

**NOTES:**

**MATERIAL**


1. Insulator Material: PBT+30%GF(UL94V-0)
2. Contact Material : Brass
3. Contact Plating :
  - (10) (9) AWP xx-7140-T : Selective 30u"Au on contact area ,Tin on soldering area over Ni
  - AWP xx-7240-T : Gold flash over Ni
  - AWP xx-7540-T : Tin over Ni
  - (8) AWP xx-7340-T : Selective 15u"Au on contact area ,Tin on soldering area over Ni

**ELECTRICAL**

1. Current Rating : 3AMP
  2. Withstand Voltage : 1000V AC/DC
  3. Contact Resistance : 20mΩ max
  4. Insulation Resistance: 1000MΩ min
- ENVIRONMENTAL**
1. Operation Temperature: -40°C to +105°C
  2. Packing: Tray

- (4) 6P Without Slot "M" and "N"
  - (7) 8P-12P With Slot "M" ,Without Slot "N"
  - 14P-64P With Slot "M" and "N"
- (6) Wire Spec: AWG28  
Pin Counts: 06,08,10,12,14,16,18,20,22,24,26,30,34,36,40,44,50,60,64

**RoHS compliant**



Scale	Free	(10)	Correct the plating to selective 30u"Au	01.11.2019	Winnie		Date	Name	Customer-No.
<b>TOLERANCE</b>		(9)	Add the plating selective 30u"Au	23.07.2019	Winnie	Drawn	25.01.2006	Alex	ASSMANN WSW-No. <b>AWP xx-7x40-T</b>
X.X	±0.40	(8)	Add the plating selective 15u"Au	07.09.2017	Winnie	Approved	01.11.2019	Winnie	
X.XX	±0.25	(7)	Update drawing	29.09.2015	Jesse				Drawing-No.
X.XXX	±0.15	(6)	Add wire spec	14.02.2014	Amy				ASS 1194C CO rev10
Angle	±3°	(5)	Add the UL-File No	13.12.2013	Winnie				Replace
		Id.	Modification	Date	Name				

