



FEATURES:

- Wire firmly held in place with internal set screw.

MATERIALS:

Upper Conn.: Miniature Banana Jack

Material: Brass per QQ-B-626, Alloy 360, 1/2 Hard.

Finish: Gold plate per MIL-G-45204, Type II, Class 00 over electroless nickel per MIL-C-26074, Class 1 (.0002/.0003).

Insulation: ABS molded to Banana Jack and Banana Plug Body.

Color: See Ordering Information

Marking: "POMONA ELECTRONICS, 2944".

Lower Conn.: Miniature Banana Plug

Material: Body – Same as above

Spring – Beryllium Copper per QQ-C-533, Berylco 25, Cond. H.T.

Finish: Same as above.

Cross Hole: 2.08 (.082) dia. with #3-56 slotted set screw to secure lead wires.

RATINGS:

Operating Temperature: +50°C. (+122°F.) Max.

Operating Voltage: 2500 VDC

Current: 5 Amperes Cont.

ORDERING INFORMATION: Model 2944-*

*=Color, -0 Black, -2 Red

Ordering Example: 2944-2 Color is Red.

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ±.005" (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies. Made in USA

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Pomona:

[2944-2](#) [2944-0](#)