

Fully Sealed Container Cermet Potentiometers Submarine Applications



FEATURES

- High power rating 1.5 W at 70 °C
- Stainless steel shaft and bushing to endure sea salt water immersion
- Fully sealed IP68 on panel
- Tight temperature coefficient (± 75 ppm/°C typical)
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912



RoHS
COMPLIANT

P13SM is designed for applications which need to set electrical parameters with an immersed potentiometer in deep water conditions up to 30 m (100 feet).

| QUICK REFERENCE DATA | |
|-------------------------|---|
| Multiple module | No |
| Switch module | n/a |
| Detent module | n/a |
| Special electrical laws | A: linear, L: logarithmic, F: reverse logarithmic |
| Sealing level | IP 68 |
| Lifespan | 25K cycles |

| DIMENSIONS in millimeters (inches) ± 0.5 mm (± 0.02 ") | |
|--|----------------------------|
| <p>P13SM N</p> | <p>Panel Cutout</p> |
| <p>P13SM B</p> | <p>Panel Cutout</p> |

Note

(1) CAUTION: Ø 1.5 of panel cut out must not be fully through-hole

Undergoes European Quality Insurance System



| ELECTRICAL SPECIFICATIONS | | |
|--|---|-----------------|
| Resistive element | Cermet | |
| Electrical travel | 270° ± 10° | |
| Resistance range | linear taper | 22 Ω to 10 MΩ |
| | logarithmic taper | 1 kΩ to 2.2 MΩ |
| Standard series E3 | 1, 2.2, 4.7, and on request 1, 2, 5 | |
| Tolerance | standard | ± 20 % |
| | on request | ± 10 % to ± 5 % |
| Taper | | |
| Circuit diagram | | |
| Power rating | <p>Linear 1.5 W at 70 °C</p> <p>Logarithmic 0.75 W at 70 °C</p> | |
| Temperature coefficient (typical) | <p>± 150 ppm/°C</p> <p>For values ≥ 100 Ω and in temperature range +20 °C to +70 °C, the typical temperature coefficient is ± 75 ppm/°C</p> | |
| Limiting element voltage (linear law) | 350 V | |
| Contact resistance variation | 3 % R _n or 3 Ω | |
| End resistance (typical) | 1 Ω | |
| Dielectric strength (RMS) | 2000 V | |
| Insulation resistance (300 V _{DC}) | 10 ⁶ MΩ | |
| Independent linearity (typical) | ± 5 % | |



| STANDARD RESISTANCE ELEMENT DATA | | | | | | | |
|----------------------------------|---------------------|----------------------|-------------------------|---------------------|----------------------|-------------------------|----------------------------------|
| STANDARD RESISTANCE VALUES | LINEAR TAPER | | | LOGS TAPED | | | TYPICAL TCR -55 °C +125 °C |
| | MAX. POWER AT 70 °C | MAX. WORKING VOLTAGE | MAX. CUR. THROUGH WIPER | MAX. POWER AT 70 °C | MAX. WORKING VOLTAGE | MAX. CUR. THROUGH WIPER | |
| Ω | W | V | mA | W | V | mA | ppm/°C |
| 22 | 1.5 | 5.74 | 261 | - | - | - | ± 150 |
| 47 | 1.5 | 8.4 | 177 | - | - | - | |
| 100 | 1.5 | 12.2 | 122 | - | - | - | |
| 220 | 1.5 | 18.2 | 82.6 | - | - | - | |
| 470 | 1.5 | 26.5 | 56.5 | - | - | - | |
| 1K | 1.5 | 38.7 | 38.7 | 0.75 | 27 | 27 | |
| 2.2K | 1.5 | 57.5 | 26.1 | 0.75 | 40 | 18 | |
| 4.7K | 1.5 | 84 | 17.9 | 0.75 | 59 | 12 | |
| 10K | 1.5 | 122.5 | 12.2 | 0.75 | 87 | 8.7 | |
| 22K | 1.5 | 182 | 8.26 | 0.75 | 128 | 5.8 | |
| 47K | 1.5 | 265 | 5.65 | 0.75 | 187 | 3.9 | |
| 100K | 1.22 | 350 | 3.5 | 0.75 | 273 | 2.7 | |
| 220K | 0.56 | 350 | 1.6 | 0.56 | 350 | 1.6 | |
| 470K | 0.26 | 350 | 0.74 | 0.26 | 350 | 0.74 | |
| 1M | 0.12 | 350 | 0.35 | 0.12 | 350 | 0.35 | |
| 2.2M | 0.05 | 350 | 0.16 | 0.05 | 350 | 0.16 | |
| 4.7M | 0.026 | 350 | 0.074 | - | - | - | |
| 10M | 0.012 | 350 | 0.035 | - | - | - | |

| MECHANICAL SPECIFICATIONS | | | |
|-----------------------------------|---------|---------------------------|-----------------------------------|
| Mechanical travel | Style B | 300° ± 5° | |
| | Style N | 310° ± 5° | |
| Operating torque (typical) | | 2 Ncm | 2.85 oz. inch |
| End stop torque | Style B | 35 Ncm max. | 3.1 lb inch max. |
| | Style N | 80 Ncm max. | 7.1 lb inch max. |
| Tightening torque of mounting nut | Style B | 80 Ncm min., 150 Ncm max. | 7 lb inch min., 13.3 lb inch max. |
| | Style N | 80 Ncm min., 250 Ncm max. | 7 lb inch min., 22.1 lb inch max. |
| Unit weight | | 8 g to 27 g | 0.3 oz. to 1 oz. |
| Terminals | | e3: pure Sn | |

| ENVIRONMENTAL SPECIFICATIONS | |
|------------------------------|---|
| Temperature range | -55 °C to +125 °C |
| Climatic category | 55 / 125 / 56 |
| Sealing | Fully sealed - container IP68 |
| Panel sealing | Immersion at 30 m (100 feet) in sea salt water or clear water |



| OPTIONS | |
|-------------------------------|--|
| Special feature command shaft | Length is measured from the mounting surface to the free end of the shaft. The screwdriver slot is aligned with the wiper within $\pm 10^\circ$. Special shafts are available, in accordance to drawings supplied by customers. We recommend that customers should not machine tool shafts, in order to avoid damage. Bending or torsion of terminals should also be avoided. |

| MARKING |
|--|
| Printed: <ul style="list-style-type: none"> • Vishay trademark • Part number (including ohmic value code, tolerance code and resistance law) • Manufacturing date • Marking of terminals a |

| PACKAGING |
|--|
| In box Packaging quantity depending on shafts: <ul style="list-style-type: none"> • Box of 5 pieces for shaft FR (code BO5) • Box of 10 pieces for shaft FG or FL (code BO10) • Box of 15 pieces for shaft BJ (code BO15) • Box of 25 pieces for shaft BB (code BO25) |

| PERFORMANCE | | | | |
|-------------------------|---|---------------------------|------------------------------|--|
| TESTS | CONDITIONS | TYPICAL VALUES AND DRIFTS | | |
| | | $\Delta R_T/R_T$ (%) | $\Delta R_{1-2}/R_{1-2}$ (%) | OTHER |
| Electrical endurance | 1000 h at rated power 90'/30' - ambient temperature 70 °C | $\pm 1 \%$ | - | Contact res. variation: $< 3 \%$ Rn |
| Climatic sequence | Phase A dry heat 125 °C Phase B damp heat Phase C cold -55 °C Phase D damp heat 5 cycles | $\pm 0.5 \%$ | $\pm 1 \%$ | - |
| Damp heat, steady state | 56 days 40 °C, 93 % HR | $\pm 0.5 \%$ | $\pm 1 \%$ | Dielectric strength: 1000 V Insulation resistance: $> 10^4 \text{ M}\Omega$ |
| Change of temperature | 5 cycles -55 °C at +125 °C | $\pm 0.5 \%$ | - | - |
| Mechanical endurance | 25 000 cycles | $\pm 3 \%$ | - | Contact res. variation: $< 2 \%$ Rn |
| Shock | 50 g's at 11 ms 3 successive shocks in 3 directions | $\pm 0.1 \%$ | $\pm 0.2 \%$ | - |
| Vibration | 10 Hz to 55 Hz 0.75 mm or 10 g's during 6 h | $\pm 0.1 \%$ | - | $\Delta V_{1-2}/V_{1-3} < \pm 0.2 \%$ |

Note

- Nothing stated herein shall be construed as a guarantee of quality or durability



| ORDERING INFORMATION (Part Number) | | | | | | | | | | | | | | | | | |
|------------------------------------|---------|------|---------|-------|----|-------------|---|---|---|--|---|---|---|---|--|--|--|
| P | 1 | 3 | S | M | N | F | L | S | 1 | 0 | 3 | M | A | E | | | |
| MODEL | BUSHING | | | SHAFT | | SHAFT STYLE | | OHMIC VALUE | | TOLERANCE | | TAPER | | SPECIAL | | | |
| P13SM | ∅ | L | Shaft ∅ | | ∅ | L | S = slotted On request: R = round F = flat D = custom | Linear law from 22 Ω to 10 MΩ Logarithmic law from 1 kΩ to 2.2 MΩ 103 = 10 kΩ | | M = 20 % On request: K = 10 % J = 5 % | | A = linear L = clockwise logarithmic F = inverse clockwise logarithmic | | E = locating peg or special code given by Vishay | | | |
| | N | 10 | 10.3 | 6 | BB | 3.17 | 12.7 | | | | | | | | | | |
| | B | 6.35 | 9.52 | 3.17 | BJ | 3.17 | 22.2 | | | | | | | | | | |
| | | | | | FG | 6 | 16 | | | | | | | | | | |
| | | | | | FL | 6 | 25 | | | | | | | | | | |
| | | | | | FR | 6 | 50 | | | | | | | | | | |
| | | | | | AP | Custom | | | | | | | | | | | |

| PART NUMBER DESCRIPTION (for information only) | | | | | | | | | | | | | |
|--|---------|---------|-------|-------------|-------|-----------|-------|---------|-----------|-------|---------|--|----------------|
| P13SM | N | E | FL | S | 10K | 20 % | A | | BO10 | | | | e3 |
| MODEL | BUSHING | SPECIAL | SHAFT | SHAFT STYLE | VALUE | TOLERANCE | TAPER | SPECIAL | PACKAGING | SHAFT | SPECIAL | | LEAD (Pb)-FREE |

| RELATED DOCUMENTS | |
|---|--|
| APPLICATION NOTES | |
| Potentiometers and Trimmers | www.vishay.com/doc?51001 |
| Guidelines for Vishay Sfernice Resistive and Inductive Components | www.vishay.com/doc?52029 |



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.