

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [0529910408](#)
Status: **Active**
Overview:
Description: 0.50mm Pitch SlimStack Receptacle, Surface Mount, Dual Row, Vertical, 3.00 and 4.00mm Stacking Heights, Lower Circuit Size Version, White, 40 Circuits

Agency Certification

UL E29179

General

Product Family PCB Receptacles
 Series [52991](#)
 Application Board-to-Board, Signal
 Overview slimstack_fine_pitch_smt_board_to_board_connectors
 Product Name SlimStack
 Series Name 0.5, BB H3/4
 UPC 800754318518

Physical

Circuits (Loaded) 40
 Circuits (maximum) 40
 Glow-Wire Capable No
 Mated Height 3.00mm, 4.00mm
 Mated Width 5.40mm
 Material - Plating Mating Gold
 Material - Plating Termination Gold
 Net Weight 161.101/mg
 Number of Rows 2
 Orientation Vertical
 PCB Locator No
 PCB Retention None
 PCB Thickness - Recommended 1.60mm
 Packaging Type Embossed Tape on Reel
 Pitch - Mating Interface 0.50mm
 Plating min - Mating 0.102µm
 Plating min - Termination 0.254µm
 Polarized to PCB No
 Surface Mount Compatible (SMC) N/A
 Temperature Range - Operating -40° to +105°C
 Termination Interface: Style Surface Mount

Electrical

Current - Maximum per Contact 0.5A
 Voltage - Maximum 50V

Material Info

Reference - Drawing Numbers

Packaging Specification 529919200-SPK-200
 Product Specification 529910000-PS-000, PS-52991-003-001, PS-52991-008-001
 Sales Drawing SD-52991-004-001, SD-52991-005-001

EU ELV

Not Relevant

EU RoHS

Compliant

REACH SVHC

Not Contained Per -
 D(2021)4569-DC (8
 July 2021)

Halogen-Free

Status

Low-Halogen

For more information, please visit [Contact US](#)

China ROHS

ELV

RoHS Phthalates

China RoHS

Green Image

Not Relevant

Not Contained

Search Parts in this Series

[52991](#) Series

Mates With

Board-to-Board SlimStack Plug [53748](#) ,
[53916](#) , [501920](#)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Molex:](#)

[52991-0408](#)