

FILAMENT SHAPE MUST BE UNIFORM WITH COILS EVENLY SPACED AND FREE OF TWIST OR SHORTING.

LTR.

DESCRIPTION

DATE

APP.

REVISIONS

BULB SHALL BE CLEAN WITH NO FOREIGN MATERIALS OR GLASS CHIPS INSIDE.

ч

- LAMPS SHALL BE CAPABLE OF OPERATION AND STORAGE AT TEMPERATURES FROM -65 °C TO +100 °C WITHOUT DEGRADATION. CENTER OF FILAMENT SHALL BE WITHIN THE CENTER 1/3 OF THE BULB.
- Ģ LAMPS SHALL BE PACKAGED IN CONTAINERS SUITABLE TO PREVENT BREAKAGE DURING SHIPMENT.
- σ LAMP BASE TO BE NICKEL PLATED D.C. BAYONET.

Superseded by Drawing # AIMTAL Rev

C-2V	1500 C	2.50	.271 ± .027	6.5	24.0
FILAME	LIFE HOURS (AVG.)	MSCP NOM.	AMPS	WATTS	VOLTS
. IN I E	. NIT	ARACTERISTICS	ELECTRICAL CHARACTERISTICS		

A14726 REV. A

B/17/96

FRACTIONAL ±X/X ANGULAR # .X 2 PLACE ±

SIN

DATE 5/17/96 /17/96

OTHERWISE SPECIFIED

3 PLACE ±

. . . . . .

T-6 D.C. BAYONET BASE LAMP

REVISION

SHEET 1 OF 1

CM8-A234

## **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

