




Optocoupler, Phototransistor Output (Dual, Quad Channel)

Dual Channel



Quad Channel



FEATURES

- Alternate source to TLP621-2, TLP621-4 and TLP621GB-2, TLP621GB-4
- High collector emitter voltage, $BV_{CEO} = 70\text{ V}$
- Dual and quad packages feature:
 - Lower pin and parts count
 - Better channel to channel CTR match
 - Improved common mode rejection
- Isolation rated voltage 4420 V_{RMS}
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912



RoHS COMPLIANT

AGENCY APPROVALS

- [UL](#)
- [cUL](#)
- [DIN EN 60747-5-5 \(VDE 0884-5\)](#), available with option 1
- [CQC GB4943.1](#)
- [CQC GB8898](#)
- [FIMKO](#)

LINKS TO ADDITIONAL RESOURCES



DESCRIPTION


The ILD621, ILQ621, ILD621GB, ILQ621GB are multi-channel phototransistor optocouplers that use GaAs IRED emitters and high gain NPN silicon phototransistors. These devices are constructed using double molded insulation technology.

The ILD621, ILQ621GB is well suited for CMOS interfacing given the CTR_{CEsat} of 30 % minimum at I_F of 1.0 mA. High gain linear operation is guaranteed by a minimum CTR_{CE} of 100 % at 5.0 mA. The ILD621, ILQ621 has a guaranteed CTR_{CE} 50 % minimum at 5.0 mA. The transparent ion shield insures stable DC gain in applications such as power supply feedback circuits, where constant DC V_{IO} voltages are present.

ORDERING INFORMATION



x = D (Dual) or Q (Quad)



| AGENCY CERTIFIED / PACKAGE | DUAL CHANNEL | | QUAD CHANNEL | |
|--------------------------------------|----------------|-----------------|----------------|-----------------|
| | CTR (%) | | | |
| UL, cUL, CSA, CQC, FIMKO | > 50 | > 100 | > 50 | > 100 |
| DIP-8 | - | ILD621GB | - | - |
| SMD-8, option 7 | ILD621-X007T | ILD621GB-X007T | - | - |
| DIP-16 | - | - | ILQ621 | ILQ621GB |
| DIP-16, option 6 | - | - | ILQ621-X006 | - |
| SMD-16, option 7 | - | - | ILQ621-X007T | - |
| SMD-16, option 9 | - | - | - | ILQ621GB-X009 |
| VDE, UL, cUL, CSA, CQC, FIMKO | > 50 | > 100 | > 50 | > 100 |
| DIP-16 | - | - | - | ILQ621GB-X001 |
| SMD-16, option 7 | - | - | - | ILQ621GB-X017T |

Note

- For additional information on the available options refer to option information



| ABSOLUTE MAXIMUM RATINGS (T _{amb} = 25 °C, unless otherwise specified) | | | | | |
|---|-------------------------|----------|-------------------|-------------|-------|
| PARAMETER | TEST CONDITION | PART | SYMBOL | VALUE | UNIT |
| INPUT | | | | | |
| Reverse voltage | | | V _R | 6.0 | V |
| Forward current | | | I _F | 60 | mA |
| Surge current | | | I _{FSM} | 1.5 | A |
| Power dissipation | | | P _{diss} | 100 | mW |
| Derate from 25 °C | | | | 1.33 | mW/°C |
| OUTPUT | | | | | |
| Collector emitter reverse voltage | | | V _{CEO} | 70 | V |
| Collector current | | | I _C | 50 | mA |
| | t < 1.0 ms | | I _C | 100 | mA |
| Power dissipation | | | P _{diss} | 150 | mW |
| Derate from 25 °C | | | | -2.0 | mW/°C |
| COUPLER | | | | | |
| Package dissipation | | ILD621 | | 400 | mW |
| | | ILD621GB | | 400 | mW |
| Derate from 25 °C | | | | 5.33 | mW/°C |
| Package dissipation | | ILQ621 | | 500 | mW |
| | | ILQ621GB | | 500 | mW |
| Derate from 25 °C | | | | 6.67 | mW/°C |
| Storage temperature | | | T _{stg} | -55 to +150 | °C |
| Operating temperature | | | T _{amb} | -55 to +100 | °C |
| Junction temperature | | | T _j | 100 | °C |
| Soldering temperature ⁽¹⁾ | 2.0 mm from case bottom | | T _{slid} | 260 | °C |

Notes

- Stresses in excess of the absolute maximum ratings can cause permanent damage to the device. Functional operation of the device is not implied at these or any other conditions in excess of those given in the operational sections of this document. Exposure to absolute maximum ratings for extended periods of the time can adversely affect reliability.
- ⁽¹⁾ Refer to reflow profile for soldering conditions for surface mounted devices (SMD). Refer to wave profile for soldering conditions for through hole devices (DIP).

| ELECTRICAL CHARACTERISTICS (T _{amb} = 25 °C, unless otherwise specified) | | | | | | | |
|---|---|----------|--------------------|------------------|------|------|------|
| PARAMETER | TEST CONDITION | PART | SYMBOL | MIN. | TYP. | MAX. | UNIT |
| INPUT | | | | | | | |
| Forward voltage | I _F = 10 mA | | V _F | 1.0 | 1.15 | 1.3 | V |
| Reverse current | V _R = 6.0 V | | I _R | - | 0.01 | 10 | µA |
| Capacitance | V _R = 0 V, f = 1.0 MHz | | C _O | - | 40 | - | pF |
| Thermal resistance, junction to lead | | | R _{THJL} | - | 750 | - | K/W |
| OUTPUT | | | | | | | |
| Collector emitter capacitance | V _{CE} = 5.0 V, f = 1.0 MHz | | C _{CE} | - | 6.8 | - | pF |
| Collector emitter leakage current | V _{CE} = 24 V | | I _{CEO} | - | 10 | 100 | nA |
| | | | I _{CEO} | - | 20 | 50 | µA |
| Thermal resistance, junction to lead | | | R _{THJL} | - | 500 | - | K/W |
| COUPLER | | | | | | | |
| Capacitance (input to output) | V _{IO} = 0 V, f = 1.0 MHz | | C _{IO} | 0.8 | - | - | pF |
| Insulation resistance | V _{IO} = 500 V | | | 10 ¹² | - | - | Ω |
| Channel to channel insulation | | | | 500 | - | - | VAC |
| Collector emitter saturation voltage | I _F = 8.0 mA, I _{CE} = 2.4 mA | ILD621 | V _{CEsat} | - | - | 0.4 | V |
| | | ILQ621 | | | | | |
| | I _F = 1.0 mA, I _{CE} = 0.2 mA | ILD621GB | V _{CEsat} | - | - | 0.4 | V |
| | | ILQ621GB | | | | | |

Note

- Minimum and maximum values are testing requirements. Typical values are characteristics of the device and are the result of engineering evaluation. Typical values are for information only and are not part of the testing requirements.



| CURRENT TRANSFER RATIO | | | | | | | |
|---|---|----------|------------------------------------|--------|------|--------|------|
| PARAMETER | TEST CONDITION | PART | SYMBOL | MIN. | TYP. | MAX. | UNIT |
| Channel/channel CTR match | $I_F = 5.0 \text{ mA}$, $V_{CE} = 5.0 \text{ V}$ | | CTR _X /CTR _Y | 1 to 1 | - | 3 to 1 | % |
| Current transfer ratio (collector emitter saturated) | $I_F = 1.0 \text{ mA}$, $V_{CE} = 0.4 \text{ V}$ | ILD621 | CTR _{CEsat} | - | 60 | - | % |
| | | ILQ621 | CTR _{CEsat} | - | 60 | - | % |
| | | ILD621GB | CTR _{CEsat} | 30 | - | - | % |
| | | ILQ621GB | CTR _{CEsat} | 30 | - | - | % |
| Current transfer ratio (collector emitter) | $I_F = 5.0 \text{ mA}$, $V_{CE} = 5.0 \text{ V}$ | ILD621 | CTR _{CE} | 50 | 80 | 600 | % |
| | | ILQ621 | CTR _{CE} | 50 | 80 | 600 | % |
| | | ILD621GB | CTR _{CE} | 100 | 200 | 600 | % |
| | | ILQ621GB | CTR _{CE} | 100 | 200 | 600 | % |

| SWITCHING CHARACTERISTICS | | | | | | | |
|---------------------------|---|-----------|------|------|------|---------------|--|
| PARAMETER | TEST CONDITION | SYMBOL | MIN. | TYP. | MAX. | UNIT | |
| NON-SATURATED | | | | | | | |
| On time | $I_F = 10 \text{ mA}$, $V_{CC} = 5.0 \text{ V}$, $R_L = 75 \Omega$, 50 % of V_{PP} | t_{on} | - | 3.0 | - | μs | |
| Rise time | $I_F = 10 \text{ mA}$, $V_{CC} = 5.0 \text{ V}$, $R_L = 75 \Omega$, 50 % of V_{PP} | t_r | - | 2.0 | - | μs | |
| Off time | $I_F = 10 \text{ mA}$, $V_{CC} = 5.0 \text{ V}$, $R_L = 75 \Omega$, 50 % of V_{PP} | t_{off} | - | 2.3 | - | μs | |
| Fall time | $I_F = 10 \text{ mA}$, $V_{CC} = 5.0 \text{ V}$, $R_L = 75 \Omega$, 50 % of V_{PP} | t_f | - | 2.0 | - | μs | |
| Propagation H to L | $I_F = 10 \text{ mA}$, $V_{CC} = 5.0 \text{ V}$, $R_L = 75 \Omega$, 50 % of V_{PP} | t_{PHL} | - | 1.1 | - | μs | |
| Propagation L to H | $I_F = 10 \text{ mA}$, $V_{CC} = 5.0 \text{ V}$, $R_L = 75 \Omega$, 50 % of V_{PP} | t_{PLH} | - | 2.5 | - | μs | |
| SATURATED | | | | | | | |
| On time | $I_F = 10 \text{ mA}$, $V_{CC} = 5.0 \text{ V}$, $R_L = 1 \text{ k}\Omega$, $V_{TH} = 1.5 \text{ V}$ | t_{on} | - | 4.3 | - | μs | |
| Rise time | $I_F = 10 \text{ mA}$, $V_{CC} = 5.0 \text{ V}$, $R_L = 1 \text{ k}\Omega$, $V_{TH} = 1.5 \text{ V}$ | t_r | - | 2.8 | - | μs | |
| Off time | $I_F = 10 \text{ mA}$, $V_{CC} = 5.0 \text{ V}$, $R_L = 1 \text{ k}\Omega$, $V_{TH} = 1.5 \text{ V}$ | t_{off} | - | 2.5 | - | μs | |
| Fall time | $I_F = 10 \text{ mA}$, $V_{CC} = 5.0 \text{ V}$, $R_L = 1 \text{ k}\Omega$, $V_{TH} = 1.5 \text{ V}$ | t_f | - | 11 | - | μs | |
| Propagation H to L | $I_F = 10 \text{ mA}$, $V_{CC} = 5.0 \text{ V}$, $R_L = 1 \text{ k}\Omega$, $V_{TH} = 1.5 \text{ V}$ | t_{PHL} | - | 2.6 | - | μs | |
| Propagation L to H | $I_F = 10 \text{ mA}$, $V_{CC} = 5.0 \text{ V}$, $R_L = 1 \text{ k}\Omega$, $V_{TH} = 1.5 \text{ V}$ | t_{PLH} | - | 7.2 | - | μs | |


| COMMON MODE TRANSIENT IMMUNITY | | | | | | | |
|------------------------------------|---|-----------------|------|------|------|------------------|--|
| PARAMETER | TEST CONDITION | SYMBOL | MIN. | TYP. | MAX. | UNIT | |
| Common mode rejection, output high | $V_{CM} = 50 V_{P-P}$, $R_L = 1.0 \text{ k}\Omega$, $I_F = 0 \text{ mA}$ | CM _H | - | 5000 | - | V/ μs | |
| Common mode rejection, output low | $V_{CM} = 50 V_{P-P}$, $R_L = 1.0 \text{ k}\Omega$, $I_F = 10 \text{ mA}$ | CM _L | - | 5000 | - | V/ μs | |

| SAFETY AND INSULATION RATINGS | | | | |
|--|---|------------|----------------|------------------|
| PARAMETER | TEST CONDITION | SYMBOL | VALUE | UNIT |
| Climatic classification | According to IEC 68 part 1 | | 55 / 100 / 21 | |
| Comparative tracking index | | CTI | 175 | |
| Maximum rated withstanding isolation voltage | $t = 1 \text{ min}$ | V_{ISO} | 4420 | V_{RMS} |
| Isolation test voltage | $t = 1.0 \text{ s}$ | V_{ISO} | 5300 | V_{RMS} |
| Maximum transient isolation voltage | | V_{IOTM} | 10 000 | V_{peak} |
| Maximum repetitive peak isolation voltage | | V_{IORM} | 890 | V_{peak} |
| Isolation resistance | $V_{IO} = 500 \text{ V}$, $T_{amb} = 25 \text{ }^\circ\text{C}$ | R_{IO} | $\geq 10^{12}$ | Ω |
| | $V_{IO} = 500 \text{ V}$, $T_{amb} = 100 \text{ }^\circ\text{C}$ | R_{IO} | $\geq 10^{11}$ | Ω |
| Output safety power | | P_{SO} | 400 | mW |
| Input safety current | | I_{SI} | 275 | mA |
| Safety temperature | | T_s | 175 | $^\circ\text{C}$ |
| Creepage distance | | | ≥ 7 | mm |
| Clearance distance | | | ≥ 7 | mm |
| Insulation thickness | | DTI | ≥ 0.4 | mm |

Note


- As per IEC 60747-5-5, § 7.4.3.8.2, this optocoupler is suitable for "safe electrical insulation" only within the safety ratings. Compliance with the safety ratings shall be ensured by means of protective circuits.

TYPICAL CHARACTERISTICS ($T_{amb} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified)




iiild621_01

Fig. 1 - Non-Saturated Switching Timing




iiild621_04

Fig. 4 - Saturated Switching Timing




iiild621_02

Fig. 2 - Non-Saturated Switching Timing




iiild621_05

Fig. 5 - Maximum LED Current vs. Ambient Temperature



iiild621_03

Fig. 3 - Saturated Switching Timing



iiild621_06

Fig. 6 - Maximum LED Power Dissipation




Fig. 7 - Forward Voltage vs. Forward Current




Fig. 10 - Propagation Delay vs. Collector Load Resistor




Fig. 8 - Collector Emitter Current vs. Temperature and LED Current




Fig. 11 - Maximum Detector Power Dissipation




Fig. 9 - Collector Emitter Leakage vs. Temperature




Fig. 12 - Maximum Collector Current vs. Collector Voltage




Fig. 13 - Normalization Factor for Non-Saturated and Saturated CTR vs. I_F




Fig. 14 - Normalization Factor for Non-Saturated and Saturated CTR vs. I_F













Fig. 15 - Normalization Factor for Non-Saturated and Saturated CTR vs. I_F




PACKAGE DIMENSIONS in millimeters




Option 6



Option 7





Option 9



18450



PACKAGE MARKING



Note

- XXXX = LMC (lot marking code)



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.