


SPECIFICATION CONTROL DRAWING

55A6262TITLE
TWO CONDUCTOR CABLE, SHIELDED, JACKETED,
LIGHTWEIGHT, 600 VOLTDate
7-17-97Revision
E

This specification sheet forms a part of the latest issue of Raychem Specification 55A and MIL-27500 as applicable.

COMPONENT WIRES - 55A0114

SHIELD - SILVER-COATED COPPER

JACKET - RADIATION-CROSSLINKED,
MODIFIED ETFE

CABLE CONSTRUCTION DETAILS

PART NUMBER	CONDUCTOR SIZE (AWG)	SHIELD SIZE (AWG)	JACKET THICKNESS (inch)		OUTSIDE DIAMETER (inch)		MAXIMUM WEIGHT (lb/1000 ft.)
			MINIMUM	MAXIMUM	NOMINAL	MAXIMUM	
55A6262-30-*	30	38	.005	.010	.081	.086	5.4
55A6262-28-*	28	38	.005	.010	.087	.092	6.3
55A6262-26-*	26	38	.005	.010	.097	.102	7.9
55A6262-24-*	24	38	.005	.010	.107	.112	9.8
55A6262-22-*	22	38	.005	.010	.119	.125	12.4
55A6262-20-*	20	38	.005	.010	.133	.142	16.4
55A6262-16-*	16	38	.006	.011	.171	.180	27.4

CABLE RATINGS AND ADDITIONAL REQUIREMENTS

TEMPERATURE RATING: 200°C

Maximum continuous conductor temperature

VOLTAGE RATING: 600 volts (rms)**AGING STABILITY: 230 ± 5°C for 96 hours****BLOCKING: 200 ± 3°C for 6 hours****CROSSLINKED VERIFICATION: 300 ± 5°C for 6 hours****DIELECTRIC WITHSTAND: 1500 volts (rms), 60 Hz****FLAMMABILITY:**Procedure 1, 3 seconds (maximum); 3 in. (maximum);
no flaming of facial tissue**JACKET COLOR: White preferred****JACKET ELONGATION AND TENSILE STRENGTH:**

Elongation, 50% (minimum)

Tensile Strength, 5000 lbf/in² (minimum)**JACKET FLAWS:**

Spark Test, 1500 volts (rms), 60 Hz, 100% test

Impulse Dielectric Test, 6.0 kV (peak), 100% test

LOW TEMPERATURE-COLD BEND: -55 ± 5°C for 4 hours**THERMAL SHOCK: 230 ± 5°C for 4 hours****SHIELD COVERAGE: 85% (minimum)****VOLTAGE WITHSTAND TEST: (POST ENVIRONMENTAL)**

1000 volts (rms), 60 Hz, 1 minute

PART NUMBER:The "*" in the part numbers above shall be replaced
by color code designators with a slash separating
the component wire colors and a dash separating
the component wire colors from the jacket color.Example: AWG 20, white and blue component wires;
white jacket: 55A6262-20-9/6-9**NOTE: Nominal values are for information only.**
Nominal values are not requirements.

This construction meets all the requirements of M27500-AWGSC2S23, AWG size 30 - 20 only, less identification.

COLORS AND COLOR CODE DESIGNATORS SHALL BE IN ACCORDANCE WITH MIL-STD-681.

DIMENSIONS ARE IN INCHES, AND UNLESS OTHERWISE DESIGNATED ARE NOMINAL.

RaychemRaychem Corporation
300 Constitution Drive, Menlo Park, California 94025
1-800-2 Raychem FAX: 1-415-361-6297

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[55A6262-22-9/96-9CS2275](#) [55A6262-26-9/96-9CS2275](#)