

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT - By -

ALL RIGHTS RESERVED.

LOCAD

DIST00

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A4	REVISED PER ECO-14-014370	23SEP2014	NK	RH

8.00
[.315]

6.00
[.236]

0.71
[.028]

0.71
[.028]

6.20
[.244]

4.50
[.177]

3.40
[.134]

3.90
[.154]

Ø3.00
[.118]

2.59
[.102]

3.10
[.122]

TERMINAL

SEE DETAIL "A"

CASE

BUTTON

COVER (GROUND)

10.01
[.394]

6.81
[.268]

5.89
[.232]

3.10
[.122]

1.40
[.055]

DETAIL "A"

SCALE 15:1

CIRCUIT DIAGRAM

12345

1,000,000

PINK

260 +/-50g

12 MM

16 MM

FSM1LPASTR

1977263-4

1,000,000

PINK

260 +/-50g

FSM1LPAS

1977263-3

1,000,000

GREEN

160 +/-50g

12 MM

16 MM

FSM1LPSTR

1977263-2

1,000,000

GREEN

160 +/-50g

FSM1LPS

1977263-1

LIFE CYCLE

ACTUATOR COLOR

ACTUATION FORCE

PITCH

TAPE WIDTH

T&B P/N

TE P/N

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
mm [INCHES]

0 PLC ± -

1 PLC ± -

2 PLC ± 0.30[.012]

3 PLC ± -

4 PLC ± -

ANGLES ± -

TOLERANCES UNLESS OTHERWISE SPECIFIED:

FINISH -

DWN
M.BINNER
24JAN08

CHK
M.SARVER
24JAN08

APVD
M.SARVER
24JAN08

PRODUCT SPEC

APPLICATION SPEC

WEIGHT -

CUSTOMER DRAWING

TE Connectivity

TACTILE SWITCH
FSM1LP

SIZE
A2

CAGE CODE
00779

DRAWING NO
C=1977263

RESTRICTED TO
-

SCALE
4:1

SHEET
1 OF 2

REV
A4

SPECIFICATIONS:

MATERIALS:
CASE, NYLON 46 UL94 V-0, IVORY
ACTUATOR, NYLON PA6T UL94V-0, SEE P/N TABLE FOR FINISH
COVER, COPPER ALLOY, TIN FINISH
TERMINAL/FIXED CONTACT, COPPER ALLOY-SILVER FINISH
MOVING CONTACT, STAINLESS STEEL-SILVER FINISH

ELECTRICAL:
MAX CONTACT RATING, 50MILLIAMP@24V DC
MIN CONTACT RATING, 1MICROAMP@1V DC
CONTACT RESISTANCE, 100 MILLIOHMS MAX
INSULATION RESISTANCE, 100 MEGOHM MIN.
DIELECTRIC STRENGTH, 500 V AC FOR 1 MINUTE
LIFE EXPECTANCY, 1,000,000 CYCLES

MECHANICAL:
ACTUATION FORCE, SEE P/N TABLE
ACTUATION TRAVEL, 0.25 +0.20/-0.10
LIFE EXPECTANCY, 1,000,000, (2 CYCLES PER SECOND AND 150% ACTUATION FORCE)

ENVIRONMENTAL:
OPERATING TEMPERATURE, -40 TO +105° C
STORAGE TEMPERATURE, -40 TO +105° C
SOLDERABILITY, EIA-RS-186-9E, OR MIL-STD-202F
RESISTANCE TO SOLDER HEAT, 260° C FOR 10SEC-PER 109-201, CONDITION B
1. NO CHANGE IN INITIAL ELECTRICAL AND MECHANICAL CHARACTERISTICS

1 ALL MATERIALS AND FINISHES SHALL COMPLY WITH EU DIRECTIVE 2002/95/EC OF 27JAN2003 (ROHS)


2 TAPE AND REEL PACKAGING PER EIA-481

1471-9 (3/11)


1977263

1977263

D




C




-THE DIMENSION OF CARRIER TAPE, COVER TAPE AND REEL-


B



A



2




D

C

B

A



THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN M.BINNER 24JAN08	TE Connectivity	
DIMENSIONS: mm [INCHES]		CHK M.SARVER 24JAN08		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD M.SARVER 24JAN08	NAME	
0 PLC ± -		PRODUCT SPEC	TACTILE SWITCH FSM1LP	
1 PLC ± -		APPLICATION SPEC	SIZE A2	
2 PLC ± 0.30[.012]		WEIGHT	CAGE CODE 00779	DRAWING NO C=1977263
3 PLC ± -		CUSTOMER DRAWING	SCALE 4:1	SHEET 2 OF 2
4 PLC ± -			REV A4	RESTRICTED TO
ANGLES ± -				
FINISH				

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[1977263-3](#)