


REV. 0

DCO 141371

COIL: @ 25°C	
RESISTANCE	4000 OHMS $\pm$ 10%
NOMINAL VOLTAGE	26.5 VDC
MUST OPERATE	12.8 VDC
TURN-ON BASE CURRENT	0.5 mADC
MUST RELEASE	8.0 VDC MAX, 1.37 VDC MIN.

ENVIRONMENT:	
VIBRATION	10 CPS TO 3000 CPS @ 30 g's
SHOCK	75 g's 6 MS. DURATION
TEMPERATURE	-65 °C TO +125 °C
NOTES: TURN-ON TIME 3.5 MS MAX	
TURN-OFF TIME 7.5 MS MAX	
CONTACT STABILIZATION TIME 2.0 MS MAX	

CUSTOMER DATA SHEET



TERMINAL VIEW

CONTACT RATING: LOW LEVEL TO 1A  
28 VDC RESISTIVE 100,000 OPERATIONS

DR. B.D. 9/20/99

*PK* 9/20/99

COMMUNICATIONS  
INSTRUMENTS, INC.

CUST. OPL  
CUST. NO. M28776/4-022P REV.

J1MST RELAY

J1MSWT-26XP

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[J1MSWT-26XP](#)