

COIL: @ 25°C
 RESISTANCE 880 OHMS ± 10%
 NOMINAL VOLTAGE 18.0 VDC
 MUST OPERATE VOLTAGE 10.5 VDC
 TURN-ON BASE CURRENT 0.16 mADC
 MUST RELEASE 6.0 VDC MAX, 0.91 VDC MIN.


ENVIRONMENT:
 VIBRATION 10 CPS TO 3000 CPS @ 30 g's
 SHOCK 75 g's 6 MS. DURATION
 TEMPERATURE -65 °C TO +125 °C

NOTES: TURN-ON TIME 2.0 MS MAX
TURN-OFF TIME 7.5 MS MAX
CONTACT STABILIZATION TIME 2.0 MS MAX

CUST. QPL
 CUST. NO. M28776/1-017P

TYPE JMAT RELAY

CUSTOMER DATA SHEET



CONTACT RATING: LOW LEVEL TO 1A
28 VDC RESISTIVE 100,000 OPERATIONS

DR. R.B. 4/16/98 *ERK* 4/16/98

COMMUNICATIONS
INSTRUMENTS, INC.

JMAWT-18XP

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[JMAWT-18XP](#)