
UNCONTROLLED DOCUMENT

PART NUMBER

LCD-S401C52TR-49


REV.

₹EV.	E.C.N.	NUMBER	AND	REVISION	COMMENTS	DA	ΙΤΕ
Α	E,C,N.	#11148.				02.0	8.07



CHARACTERISTICS							
FLUID TYPE:	TN						
BACKGROUND COLOR:	GRAY						
VIEWING DIRECTION:	6:00						
DISPLAY MODE:	REFLECTIVE						
OPERATING VOLTAGE:	5.0V AC.						
OPERATING TEMP.	0°C T0 50°C						
STORAGE TEMP.	-20°C TO 70°C						
DRIVING METHODE:	STATIC						
CONNECTION TYPE:	40 PINS						

CHARACTER DETAIL



P	NO.	1	2	3	4	5	6	7	8	9	10
S	EGMENT	COM	N/C	N/C	N/C	1E	1 D	1C	DP1	2E	20
F	NO.	11	12	13	14	15	16	17	18	19	20
S	EGMENT	20	DP2	3E	3D	3C	DP3	4E	4D	4C	4B
F	NO.	21	22	23	24	25	26	27	28	29	30
S	EGMENT	4A	4F	4G	3B	3A	3F	3C	ΩL	28	2A
P	'IN NO.	31	32	33	34	35	36	37	38	39	40
S	EGMENT	2F	2G	N/C	1B	1 A	1F	1G	N/C	N/C	СОМ

UNCONTROLLED DOC **UNLESS DTHERWISE SPECIFIED TOLERANCES PER DECINAL PRECISION ARE: X=±1 (±0.039), XX=±0.5 (±0.020), XXX=±0.25 (±0.010), XXXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MN= +DECINAL PRECISION MAX.= +0.00 (±0.004), XXX=±0.127 (±0.005).

REV. PART NUMBER LCD-S401C52TR-49

0.52" CHARACTER HEIGHT, FOUR DIGIT LCD GLASS, TN, REFLECTIVE, 40 PINS, ,49" PIN LENGTH.

CONFIDENTIAL INFORMATION
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX NC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD PALATINE, IL 60067-6976 PHONE: +1.847.359,2790 US WEB: www.lumex.com TW WEB: www.lumex.com.tw

CHECKED BY: APPROVED BY: DRAWN BY: DATE: 10.2.01 PAGE: 1 OF 1 SCALE: N/A JC

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Lumex:

LCD-S401C52TR-49