


OR-ing Power Schottky Rectifier


Non isolated

$$\begin{aligned} I_{FAVM} &= 2 \times 200 \text{ A} \\ V_{RRM} &= 8 \text{ V} \\ V_F &= 0.15 \text{ V} \end{aligned}$$

V_{RSM}	V_{RRM}	Type
V	V	
8	8	DSS 2x200-0008D



miniBLOC, SOT-227 B



Common cathode

Symbol	Conditions	Maximum Ratings	
I_{FRMS}		200	A
I_{FAVM}	$T_C = 100^\circ\text{C}$; rectangular, $d = 0.5$	200	A
I_{FAVM}	$T_C = 100^\circ\text{C}$; rectangular, $d = 0.5$; per device	400	A
I_{FSM}	$T_{VJ} = 45^\circ\text{C}$; $t_p = 10 \text{ ms}$ (50 Hz), sine	1600	A
E_{AS}	$I_{AS} = \text{tbd}$; $L = 180 \mu\text{H}$; $T_{VJ} = 25^\circ\text{C}$; non repetitive	tbd	mJ
I_{AR}	$V_A = 1.5 \cdot V_{RRM}$ typ.; $f = 10 \text{ kHz}$; repetitive	tbd	A
$(dv/dt)_{cr}$		5000	V/ μs
T_{VJ}		-40...+150	$^\circ\text{C}$
T_{VJM}		150	$^\circ\text{C}$
T_{stg}		-40...+150	$^\circ\text{C}$
P_{tot}	$T_C = 25^\circ\text{C}$	310	W
M_d	mounting torque (M4)	1.1-1.5/9-13	Nm/lb.in.
	terminal connection torque (M4)	1.1-1.5/9-13	Nm/lb.in.
Weight	typical	30	g

Features

- International standard package miniBLOC
- Epoxy meets UL 94V-0
- Very low V_F
- Extremely low switching losses
- Low I_{RM} -values

Applications

- Rectifiers in switch mode power supplies (SMPS)
- Free wheeling diode in low voltage converters

Advantages

- High reliability circuit operation
- Low voltage peaks for reduced protection circuits
- Low noise switching
- Low losses

Dimensions see IXYS Data Book 2001
pages D2 - 87-88

Symbol	Conditions	Characteristic Values	
		typ.	max.
I_R ①	$T_{VJ} = 25^\circ\text{C}$; $V_R = V_{RRM}$ $T_{VJ} = 100^\circ\text{C}$; $V_R = V_{RRM}$	400 3000	mA mA
V_F	$I_F = 100 \text{ A}$; $T_{VJ} = 125^\circ\text{C}$ $T_{VJ} = 25^\circ\text{C}$ $I_F = 200 \text{ A}$; $T_{VJ} = 125^\circ\text{C}$ $I_F = 100 \text{ A}$; $T_{VJ} = 150^\circ\text{C}$; per device	0.23 0.34 0.34 0.15	V V V V
R_{thJC} R_{thCH}	0.15	0.4	K/W K/W

Pulse test: ① Pulse Width = 5 ms, Duty Cycle < 2.0 %
Data according to IEC 60747 and per diode unless otherwise specified

IXYS reserves the right to change limits, Conditions and dimensions.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[IXYS:](#)

[DSS2x200-0008D](#)