

		В
	(Ĭ
ζ		

PIN PL	ATING CODES:										
XXXXX-1YY	30u"/0.76u MIN (SEE NOTE 14) OVER 50u"/1.27u MIN Ni										
XXXXX-2YY	15u"/0.38u MIN (SEE NOTE 14) OVER 50u"/1.27u MIN Ni										
XXXXX-3YY	50u"/1.27u MIN (SEE NOTE 14) OVER 50u"/1.27u MIN Ni										
XXXXX-4YY	100u"/2.54u MIN Sn OVER 50u"/1.27u MIN Ni (SEE NOTE 15)										
XXXXX-4YYHLF	1000 / 2.0 TO WIN 311 OVER 300 / 1.2/0 WIN NI (SEE NOTE 13)										
XXXXX-5YY	15u"/0.38u MIN (SEE NOTE 14) OVER 50u"/1.27u MIN Ni										
XXXXX-6YY	30u"/0.76u MIN (SEE NOTE 14) OVER 50u"/1.27u MIN Ni										
XXXXX-7YY	30u"/0.76u MIN (SEE NOTE 14) OVER 50u"/1.27u MIN NI										
XXXXX-8YY	15u"/0.38u MIN (SEE NOTE 14) OVER 50u"/1.27u MIN Ni										
XXXXX-9YY	15u"/0.38u MIN (SEE NOTE 14) OVER 50u"/1.27u MIN Ni										
XXXXX-0YY	30u"/0.76u MIN (SEE NOTE 14) OVER 50u"/1.27u MIN Ni										

NOTES

1. PART NUMBER OPTIONS:

PIN PLATING CODES (SEE ABOVE)

HIGH TEMPERATURE MATERIAL:

PART NUMBERS WITH AND WITHOUT "H" WILL BE SUPPLIED WITH HIGH TEMPERATURE PLASTIC.

NUMBER OF POSITIONS:

EVEN NUMBER OF POSITIONS FROM 2 (2X1) THROUGH 72 (2X36). -X00H INDICATES BERGSTRIP PRODUCT. SEE PAGE 3 FOR SPECIAL GEOMETRY OF THIS CONTINUOUS STRIP PRODUCT. AUTOMATED REELS WILL CONTAIN 45,000 PINS. SEE SPECIFIC PART NUMBERS FOR AVAILABILITY.

PACKAGING:

PACKAGED IN POLY BAGS.

EIGHT DIGIT PART NUMBERS FOLLOWED BY A "T" ARE PACKAGED IN TUBES. SEE SPECIFIC PART NUMBERS FOR AVAILABILITY.

EIGHT DIGIT PART NUMBERS FOLLOWED BY A "G" ARE PACKAGED IN GPAX FOR IBM ONLY. SEE SPECIFIC PART NUMBERS FOR AVAILABILITY.

PART NUMBERS FOLLOWED BY A "C" ARE PACKAGED IN TUBES WITH A PICKUP CAP APPLIED.

EIGHT DIGIT PART NUMBERS FOLLOWED BY A "A" ARE PACKAGED IN TAPE/REEL WITH PICKUP CAP P/N 95730-003 APPLIED.

LEAD FREE:

ADD "HLF" SUFFIX AT THE END OF PART NUMBER FOR LEAD FREE OPTION, NOT AVAILABLE FOR -5YY, -5YYH, -6YY & -6YYH

HALOGEN FREE:

ADD "HF" SUFFIX AT THE END OF PART NUMBER FOR HOLOGEN FREE OPTION

2. BODY MATERIAL:

BODY MATERIAL: MANUFACTURER'S OPTION OF NYLON, PCT GLASS FIBER REINFORCED OR MINERAL FILLED LCP FLAME RETARDENT PER UL-94V-0. COLOR: BLACK

BERGSTRIP™PRODUCED WITH HIGH TEMPERATURE LCP THERMOPLASTIC, FLAME RETARDENT PER UL-94V-O. COLOR: BLACK

1

PART NUMBERS WITH "H" AND WITHOUT SUFFIX WILL WITHSTAND EXPOSURE TO 260° C PEAK TEMPERATURE FOR 20 SECONDS IN WAVE SOLDER, INFRA-RED OR VAPOR PHASE SOLDER PROCESS.

- 3. PIN MATERIAL: PHOS BRONZE.
- 4. MEASURED WITH PART IN RESTRAINED CONDITION.
- 5. TWO SIDES OF PIN TIPS NOT PLATED. TYPICAL BOTH ENDS
- 6. 2LBS/0.9KG MIN PIN RETENTION IN EITHER DIRECTION.
- 7. MILITARY BERGSTIK HEADER P/N XXXXX-XYY-MIL NOT AVAILABLE.
- 8. ±.010/0.25 TOL APPLIES TO ALL "G" TAILS EXCEPT INDICATED PARTS ON TABLE WHERE +.010/0.25 -.000/0.00 APPLIES.
- 9. NOTCH CONFIGURATION WILL VARY PER VENDOR'S DISCRETION.
- 10. BERGSTRIP™ PART NUMBERS FOLLOWED BY BY A "B" ARE BULK PRICED.
- 11. TAIL LENGTH (DIM. G) TO BE ±.008/.0.20.
- 12. POSITIONS PER ROW 37 TO 50 CAN BE PRODUCED, BUT FLATNESS AND CURVATURE MAY NOT BE HELD AS CLOSE AS 36 POSITIONS.
- 13. THESE PRODUCTS MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATION AS DESCRIBED IN GS-22-008.
- 14. PLATING OPTIONS:

 PERFORMANCE PLATING WILL BE EITHER GOLD OR GXT ON POST OR TAIL,

 OPTIONALLY (78~295u"/2~7.5u) TIN ON TAIL.
- 15. "THIS PRODUCT HAS 100% TIN PLATING IN THE INTERFACE AND HAS NOT BEEN TESTED FOR WHISKER GROWTH IN ALL INTERCONNECT ENVIRONMENTS."
- 16. THE OAL DON'T EXCEED 34.5mm
- 17. INCREMENTS BY 0.1mm IN LENGTHS ONLY
- 18. FOR SPECIAL PACKAGING REQUEST PLEASE CONTACT PRODUCT MANAGER FOR AVAILABILITY
- 19. TO DETERMINE DIMENSIONS:
 N=NUMBER OF POSITION PER ROW
 EXAMPLE: 10 POS. N X .100/2.54
- 20. PART NUMBERS 68602 OR 67996 FOLLOWED BY A "D" ARE PACKAGED IN TAPE/REEL WITHOUT PICKUP CAP.

	index sheet 1-8			4 6	יפחי	Rev	/ ·DI	K			STA	TUS	∶Re	eas	ed		Prin	nted	· No	ov 10	6, 2 0	D		
she	eet	revi	sion	DK																				ĺ
				appd	T.	напр	IA 07/21/99				type Product				Customer Drawin			ing	ĺ					
						chr	J.MURPHY			07/21/99		FCi						0 / 3	990				Н3	ĺ
						engr	r T.HANNA (07/21/99			Amphenol FCi					670	996				Аз	ĺ	
						dr	T.BR	EWB/			1/94				dwg	nc)		S	heet	:2 c	of 8	size	ŀ
						0°±2	2*	.xxxx±0			XXXX±0.0020/.XXX±0.051			: 1		.10	10/2	2.54	СС	C STRAIGHT				ĺ
						ğ	il 🔄	near	.xxx±0.005/.xx±0.13						.100/2.54cc STRAIGHT							İ		
DK						angles .			.xx±0.01/0.3			INC	CH/I	ИΜ	BERGSTIK II HEADER D/F						'R	İ		
ltr	ecr	n no	dr	dat	(I)	tolerances unless otherwise specified						y	9 -	7	title									ĺ
S	EE N	NOTE	S	1 &	2	ISO 1302 V ISO 406 ISO 11					1101	⊕ ←			BERGSTIK									ĺ
mc	ıt'l.	code				surface / tolerance					pro	jecti	on	product family									ĺ	

form: A3-2016-02-24

2











