

PCB terminal block - 1931602

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



PCB terminal block, nom. voltage: 160 V, pitch: 3.81 mm, number of positions: 12, connection method: Push-in spring connection, mounting: Wave soldering, color: green

The figure shows a 1-pos. version of the product

Your advantages

- Time saving push-in connection, tools not required
- Defined contact force ensures that contact remains stable over the long term
- Intuitive use through colour coded actuation lever
- Operation and conductor connection from one direction enable integration into front of device
- Two solder pins reduce the mechanical strain on the soldering spots
- The latching on the side enables various numbers of positions to be combined



Key Commercial Data

Packing unit	1
--------------	---

Technical data

Dimensions

Length [l]	13.65 mm
Pitch	3.81 mm
Dimension a	41.91 mm
Width [w]	48.22 mm
Height	12.7 mm
Height [h]	16.1 mm
Solder pin [P]	3.4 mm
Pin spacing	5.08 mm
Hole diameter	1.3 mm

General

Range of articles	FFKDS(A) 1,5/..-H
Nominal cross section	1 mm ²

PCB terminal block - 1931602

Technical data

General

Number of positions	12
---------------------	----

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Phoenix Contact:](#)

[1931602](#)