

## Printed-circuit board connector - FK-MC 0,5/ 2-ST-2,5 KMGYLP:-, + - 1706260

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)


PCB connector, nominal current: 4 A, number of positions: 2, pitch: 2.5 mm, connection method: Push-in spring connection, color: light gray, contact surface: Tin



The figure shows a 10-position version of the product

### Your advantages

- ✓ Time saving push-in connection, tools not required
- ✓ Defined contact force ensures that contact remains stable over the long term
- ✓ Intuitive use through colour coded actuation lever
- ✓ Operation and conductor connection from one direction enable integration into front of device
- ✓ Quick and convenient testing using integrated test option



### Key Commercial Data

|              |                                                                                                         |
|--------------|---------------------------------------------------------------------------------------------------------|
| Packing unit | 50 pc                                                                                                   |
| GTIN         | <br>4 046356 033022 |
| GTIN         | 4046356033022                                                                                           |

### Technical data

#### Item properties

|                           |                                 |
|---------------------------|---------------------------------|
| Brief article description | Printed-circuit board connector |
| Plug-in system            | MICRO COMBICON - FK-MC 0,5      |
| Type of contact           | Female connector                |
| Range of articles         | FK-MC 0,5/...-ST                |
| Pitch                     | 2.5 mm                          |
| Number of positions       | 2                               |
| Connection method         | Push-in spring connection       |
| Locking                   | without                         |
| Number of levels          | 1                               |

# Printed-circuit board connector - FK-MC 0,5/ 2-ST-2,5 KMGYLP:-, + - 1706260

## Technical data

### Electrical parameters

|                                  |        |
|----------------------------------|--------|
| Rated current                    | 4 A    |
| Rated insulation voltage (III/2) | 160 V  |
| Rated surge voltage (III/2)      | 2.5 kV |

### Connection capacity

|                                                                       |                                              |
|-----------------------------------------------------------------------|----------------------------------------------|
| Conductor cross section solid                                         | 0.14 mm <sup>2</sup> ... 0.5 mm <sup>2</sup> |
| Conductor cross section flexible                                      | 0.14 mm <sup>2</sup> ... 0.5 mm <sup>2</sup> |
| Conductor cross section AWG / kcmil                                   | 26 ... 20                                    |
| Conductor cross section flexible, with ferrule without plastic sleeve | 0.25 mm <sup>2</sup> ... 0.5 mm <sup>2</sup> |
| Cylindrical gauge a x b / diameter                                    | - / 1.4 mm                                   |
| Stripping length                                                      | 8 mm                                         |

### Material data - contact

|                                          |                                                                                   |
|------------------------------------------|-----------------------------------------------------------------------------------|
| Note                                     | WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/ JEDEC JESD 201 |
| Contact material                         | Cu alloy                                                                          |
| Surface characteristics                  | hot-dip tin-plated                                                                |
| Metal surface terminal point (top layer) | Tin (4 - 8 µm Sn)                                                                 |
| Metal surface contact area (top layer)   | Tin (4 - 8 µm Sn)                                                                 |

### Material data - housing

|                                                                   |        |
|-------------------------------------------------------------------|--------|
| Insulating material                                               | PA     |
| Insulating material group                                         | I      |
| CTI according to IEC 60112                                        | 600    |
| Flammability rating according to UL 94                            | V0     |
| Glow wire flammability index GWFI according to EN 60695-2-12      | 850    |
| Glow wire ignition temperature GWIT according to EN 60695-2-13    | 775    |
| Temperature for the ball pressure test according to EN 60695-10-2 | 125 °C |

### Material data – actuating element

|                                        |     |
|----------------------------------------|-----|
| Insulating material                    | POM |
| CTI according to IEC 60112             | 600 |
| Flammability rating according to UL 94 | HB  |

### Dimensions for the product

|                             |                                                                                                         |
|-----------------------------|---------------------------------------------------------------------------------------------------------|
| Caption                     | Schematic representation – for additional information, see product range drawing in the Download Center |
| Length [ l ]                | 19.05 mm                                                                                                |
| Width [ w ]                 | 5.6 mm                                                                                                  |
| Height [ h ]                | 11.75 mm                                                                                                |
| Pitch                       | 2.5 mm                                                                                                  |
| Height (without solder pin) | 11.75 mm                                                                                                |
| Dimension a                 | 2.5 mm                                                                                                  |

# Printed-circuit board connector - FK-MC 0,5/ 2-ST-2,5 KMGYLP:-, + - 1706260

## Technical data

### Packaging information

|                            |                     |
|----------------------------|---------------------|
| Type of packaging          | packed in cardboard |
| Pieces per package         | 50                  |
| Denomination packing units | Pcs.                |

### General product information

|              |                                                                                                                                                                                          |
|--------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Type of note | Notes on operation                                                                                                                                                                       |
| Note         | In accordance with IEC 61984, COMBICON connectors have no switching power (COC). During designated use, they must not be plugged in or disconnected when carrying voltage or under load. |

### Ambient conditions

|                                         |                  |
|-----------------------------------------|------------------|
| Ambient temperature (storage/transport) | -40 °C ... 70 °C |
| Ambient temperature (assembly)          | -5 °C ... 100 °C |
| Ambient temperature (operation)         | -40 °C           |

### Termination and connection method

|                                          |                                                                                                                                               |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| Conductor connection test                | The stripped-off ends of the largest conductor can be completely inserted in the opening of the terminal point without using excessive force. |
| Test result                              | Test passed                                                                                                                                   |
| Test – repeated connection and release   | IEC 60999-1:1999-11                                                                                                                           |
|                                          | Test passed                                                                                                                                   |
| Test for conductor damage and slackening | IEC 60999-1:1999-11                                                                                                                           |
|                                          | Test passed                                                                                                                                   |

### Pull-out test

|                                                          |                                         |
|----------------------------------------------------------|-----------------------------------------|
| Pull-out test                                            | IEC 60999-1:1999-11                     |
|                                                          | Test passed                             |
| Conductor cross section / conductor type / tensile force | 0.2 mm <sup>2</sup> / solid / > 10 N    |
|                                                          | 0.2 mm <sup>2</sup> / flexible / > 10 N |
|                                                          | 0.5 mm <sup>2</sup> / solid / > 20 N    |
|                                                          | 0.5 mm <sup>2</sup> / flexible / > 20 N |

### Mechanical tests according to standard

|                                     |                                    |
|-------------------------------------|------------------------------------|
| Test specification                  | IEC 61984                          |
| Visual examination                  | Test passed IEC 60512-1-1:2002-02  |
| Dimensional test                    | Test passed IEC 60512-1-2:2002-02  |
| Resistance of marking               | Test passed IEC 60068-2-70:1995-12 |
| Result                              | Test passed                        |
| Specification                       | IEC 60512-13-2:2006-02             |
| No. of cycles                       | 25                                 |
| Insertion strength per pos. approx. | 8 N                                |
| Withdraw strength per pos. approx.  | 6 N                                |

# Printed-circuit board connector - FK-MC 0,5/ 2-ST-2,5 KMGYLP:-, + - 1706260

## Technical data

### Mechanical tests according to standard

|                         |                                    |
|-------------------------|------------------------------------|
| Polarization and coding | Test passed IEC 60512-13-5:2006-02 |
| Result                  | Test passed                        |
| Specification           | IEC 60512-15-1:2008-05             |
| Test force per pos.     | 24 N                               |

### Air clearances and creepage distances

|                                  |                                               |
|----------------------------------|-----------------------------------------------|
| Specification                    | IEC 60664-1:1992-10 + A1:2000-02 + A2:2002-05 |
| Insulating material group        | I                                             |
| Voltage                          | 100 V                                         |
| Rated insulation voltage (III/3) | 100 V                                         |
| Rated insulation voltage (III/2) | 160 V                                         |
| Rated insulation voltage (II/2)  | 320 V                                         |
| Rated surge voltage (III/3)      | 1.5 kV                                        |
| Rated surge voltage (III/2)      | 2.5 kV                                        |
| Rated surge voltage (II/2)       | 2.5 kV                                        |

### Electrical tests - Function

|               |                     |
|---------------|---------------------|
| Specification | IEC 60999-1:1999-11 |
|---------------|---------------------|

### Temperature cycles

|                                      |                     |
|--------------------------------------|---------------------|
| Specification                        | IEC 60999-1:1999-11 |
| Test current (minimum cross section) | 4 A                 |
| Test current (maximum cross section) | 6 A                 |
| Temperature cycles                   | 192                 |

### Current carrying capacity / derating curves

|               |           |
|---------------|-----------|
| Specification | IEC 61984 |
|---------------|-----------|

### Mechanical tests (A)

|                                              |             |
|----------------------------------------------|-------------|
| Test specification                           | IEC 61984   |
| Insertion strength per pos. approx.          | 8 N         |
| Withdraw strength per pos. approx.           | 6 N         |
| Polarization when inserted requirement >20 N | Test passed |
| Contact holder in insert requirements >20 N  | Test passed |

### Durability tests (B)

|                                              |                       |
|----------------------------------------------|-----------------------|
| Specification                                | IEC 60512-9-1:2010-03 |
| Contact resistance R <sub>1</sub>            | 2 mΩ                  |
| Insertion/withdrawal cycles                  | 25                    |
| Contact resistance R <sub>2</sub>            | 2.2 mΩ                |
| Impulse withstand voltage at sea level       | 2.95 kV               |
| Power-frequency withstand voltage            | 1.39 kV               |
| Insulation resistance, neighboring positions | 80 GΩ                 |

# Printed-circuit board connector - FK-MC 0,5/ 2-ST-2,5 KMGYLP:-, + - 1706260

## Technical data

### Climatic tests (D)

|                                        |                                                                           |
|----------------------------------------|---------------------------------------------------------------------------|
| Specification                          | ISO 6988:1985-02                                                          |
| Cold stress                            | -40 °C/2 h                                                                |
| Thermal stress                         | 100 °C/168 h                                                              |
| Corrosive stress                       | 0.2 dm <sup>3</sup> SO <sub>2</sub> on 300 dm <sup>3</sup> /40 °C/1 cycle |
| Impulse withstand voltage at sea level | 2.95 kV                                                                   |
| Power-frequency withstand voltage      | 1.39 kV                                                                   |

### Environmental and durability tests (E)

|                                       |                                     |
|---------------------------------------|-------------------------------------|
| Specification                         | IEC 61984:2008-10                   |
| Result, degree of protection, IP code | Finger safety with IP20 test finger |

### Environmental Product Compliance

|            |                                                         |
|------------|---------------------------------------------------------|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |

## Approvals

### Approvals

#### Approvals

CCA / IEC EE CB Scheme / VDE Gutachten mit Fertigungsüberwachung / EAC / cULus Recognized

#### Ex Approvals

### Approval details

|                            |                |
|----------------------------|----------------|
| CCA                        | CCA/ DE1 34250 |
| Nominal voltage UN         | 100 V          |
| Nominal current IN         | 4 A            |
| mm <sup>2</sup> /AWG/kcmil | 0.2-.5         |

|                            |                     |                                                           |                |
|----------------------------|---------------------|-----------------------------------------------------------|----------------|
| IECEE CB Scheme            | <b>CB</b><br>scheme | <a href="http://www.iecee.org/">http://www.iecee.org/</a> | DE1-56068-B1B2 |
| Nominal voltage UN         | 100 V               |                                                           |                |
| Nominal current IN         | 4 A                 |                                                           |                |
| mm <sup>2</sup> /AWG/kcmil | 0.2-.5              |                                                           |                |

## Printed-circuit board connector - FK-MC 0,5/ 2-ST-2,5 KMGYLP:-, + - 1706260

### Approvals

|                                            |                                                                                   |                                                                                                                                                                                                                |          |
|--------------------------------------------|-----------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|
| VDE Gutachten mit<br>Fertigungsüberwachung |  | <a href="http://www2.vde.com/de/Institut/Online-Service/VDE-gepruefteProdukte/Seiten/Online-Suche.aspx">http://www2.vde.com/de/Institut/Online-Service/<br/>VDE-gepruefteProdukte/Seiten/Online-Suche.aspx</a> | 40013394 |
|                                            |                                                                                   |                                                                                                                                                                                                                |          |
| Nominal voltage UN                         | 100 V                                                                             |                                                                                                                                                                                                                |          |
| Nominal current IN                         | 4 A                                                                               |                                                                                                                                                                                                                |          |
| mm²/AWG/kcmil                              | 0.2-.5                                                                            |                                                                                                                                                                                                                |          |

|     |                                                                                   |         |
|-----|-----------------------------------------------------------------------------------|---------|
| EAC |  | B.01742 |
|-----|-----------------------------------------------------------------------------------|---------|

|                    |  |                                                                                    |                                                                                                                                                       |                 |
|--------------------|--|------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| cULus Recognized   |  |  | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> | E60425-19930913 |
|                    |  | B                                                                                  |                                                                                                                                                       |                 |
| Nominal voltage UN |  |                                                                                    |                                                                                                                                                       |                 |
| Nominal current IN |  |                                                                                    |                                                                                                                                                       |                 |
| mm²/AWG/kcmil      |  |                                                                                    |                                                                                                                                                       |                 |

Phoenix Contact 2018 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Phoenix Contact:](#)

[1706260](#)