


7	101.19 [3.984]	99.06 [3.900]	39	40	9-146291-0	
7	98.65 [3.884]	96.52 [3.800]	38	39	8-146291-9	
7	96.11 [3.784]	93.98 [3.700]	37	38	8-146291-8	
7	93.57 [3.684]	91.44 [3.600]	36	37	8-146291-7	
7	91.03 [3.584]	88.90 [3.500]	35	36	8-146291-6	
7	88.49 [3.484]	86.36 [3.400]	34	35	8-146291-5	
7	85.95 [3.384]	83.82 [3.300]	33	34	8-146291-4	
7	83.41 [3.284]	81.28 [3.200]	32	33	8-146291-3	
7	80.87 [3.184]	78.74 [3.100]	31	32	8-146291-2	
7	78.33 [3.084]	76.20 [3.000]	30	31	8-146291-1	
7	75.79 [2.984]	73.66 [2.900]	29	30	8-146291-0	
7	73.25 [2.884]	71.12 [2.800]	28	29	7-146291-9	
7	70.71 [2.784]	68.58 [2.700]	27	28	7-146291-8	
7	68.17 [2.684]	66.04 [2.600]	26	27	7-146291-7	
7	65.63 [2.584]	63.50 [2.500]	25	26	7-146291-6	
7	63.09 [2.484]	60.96 [2.400]	24	25	7-146291-5	
7	60.55 [2.384]	58.42 [2.300]	23	24	7-146291-4	
7	58.01 [2.284]	55.88 [2.200]	22	23	7-146291-3	
7	55.47 [2.184]	53.34 [2.100]	21	22	7-146291-2	
7	52.93 [2.084]	50.80 [2.000]	20	21	7-146291-1	
7	50.39 [1.984]	48.26 [1.900]	19	20	7-146291-0	
7	47.85 [1.884]	45.72 [1.800]	18	19	6-146291-9	
7	45.31 [1.784]	43.18 [1.700]	17	18	6-146291-8	
7	42.77 [1.684]	40.64 [1.600]	16	17	6-146291-7	
7	40.23 [1.584]	38.10 [1.500]	15	16	6-146291-6	
7	37.69 [1.484]	35.56 [1.400]	14	15	6-146291-5	
7	35.15 [1.384]	33.02 [1.300]	13	14	6-146291-4	
7	32.61 [1.284]	30.48 [1.200]	12	13	6-146291-3	
7	30.07 [1.184]	27.94 [1.100]	11	12	6-146291-2	
7	27.53 [1.084]	25.40 [1.000]	10	11	6-146291-1	
7	24.99 [.984]	22.86 [.900]	9	10	6-146291-0	
7	22.45 [.884]	20.32 [.800]	8	9	5-146291-9	
7	19.91 [.784]	17.78 [.700]	7	8	5-146291-8	
7	17.37 [.684]	15.24 [.600]	6	7	5-146291-7	
7	14.83 [.584]	12.70 [.500]	5	6	5-146291-6	
7	12.29 [.484]	10.16 [.400]	4	5	5-146291-5	
7	9.75 [.384]	7.62 [.300]	3	4	5-146291-4	
7	7.21 [.284]	5.08 [.200]	2	3	5-146291-3	
PLATING		C	B	A	NO OF POSITIONS	PART NUMBER

OBSOLETE

THIS DRAWING IS A CONTROLLED DOCUMENT.		DIN T. HOFFMAN 12/6/95		 TE Connectivity	
DIMENSIONS: mm [INCHES]		TOLERANCES UNLESS OTHERWISE SPECIFIED:			
0 PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± - 4 PLC ± - ANGLES ± -		C/K G. DUBNICZKI 2/1/96 AP/PO G. DUBNICZKI 2/1/96 PRODUCT SPEC		NAME: HEADER ASSEMBLY, MOD II, BREAKAWAY, SINGLE ROW, HIGH TEMPERATURE, VERTICAL WITH RETENTION FEATURE, W/.025 SQ. POSTS, .100 C/L APPLICATION SPEC	
MATERIAL FINISH SEE TABLE		WEIGHT -		SIZE: A1 CAGE CODE: 00779 DRAWING NO: 146291 RESTRICTED TO: -	
CUSTOMER DRAWING				SCALE: 4:1 SHEET 2 OF 2 REV J	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[9-146291-0](#)