muRata Capacitor Data Sheet RCER72A681K0M1H03A "#" indicates a package specification code.							
In Pr	In Production Power- train Q200 125 Cmax. Deflecting Crack Deflecting Crack Soldering Crack Reach						
	< List of part numbers with package codes > RCER72A681K0M1H03A						
	Shape		Notes				
	L. T.	P	Meet LF(Lead Free)[*LF : Lead content is less than 1000 ppm.], HF(Halogen Free)				
			References				
			Packaging	Specifications	Minimum quantity		
			А	Ammo pack taping type	2000		
	تل) ۲۰۰۰ (in mm)						
Ls	ize or outer diameter D (mm)	3.6 mm max.					
W	size	3.5 mm max.					
Ts	ize	2.5 mm max.					
Lea	Lead spacing F 5.0 +0.6/-0.2mm						

0.5 ±0.05mm

6.0mm

Specifications

Lead diameter d

W1 size (max.)

Capacitance	680pF±10%
Rated voltage	100Vdc
Temperature characteristics (complied standard)	X7R(EIA)
Capacitance change rate	±15%
Temperature range of temperature characteristics	-55 to 125°C
Operating temperature range	-55 to 125°C

🔔 Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications. Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.