

XUB1BNANL2

photo-electric sensor - XUB - reflex - Sn 4m -
12..24VDC - cable 2m



Main

Range of product	OsiSense XU
Series name	Optimum
Specific app photo-elec dtctr	Object
Sensor name	XUB
Sensor design	M18
Material	Metal
Detection system	Reflex
Emission	Infrared reflex
Line of sight type	Axial
[Sn] nominal sensing distance	4 m reflex
Wiring techniques	3 wires
Type of output signal	Discrete
Output type	Solid state
Discrete output function	1 NO
Discrete output type	NPN
Add on output	Without
Electrical connection	Cable
Cable length	2 m
Wire insulation material	PvR
Supply circuit type	DC
Us rated supply voltage	12...24 V DC with reverse polarity protection
Switching capacity in mA	<= 100 mA, overload and short-circuit protection
Diameter	18 mm

Complementary

Electronic sensor type	Photo-electric sensor
Enclosure material	Nickel plated brass
Lens material	PMMA
Maximum sensing distance	5.5 m reflex
Status LED	1 LED (yellow) for output state
Supply voltage limits	10 - 36 V DC
Switching frequency	<= 500 Hz
Voltage drop	1.5 V (closed state)
Current consumption	35 mA at no-load
Delay first up	< 15 ms
Delay response	< 1 ms
Delay recovery	< 1 ms
Setting-up	Without sensitivity adjustment
Length	46 mm
CAD overall width	18 mm
CAD overall height	18 mm
CAD overall depth	64 mm

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

Product certifications	CE CSA UL
Ambient air temp for op	-25...55 °C
Ambient air temp for storage	-40...70 °C
Vibration resistance	7 gn, amplitude +/- 1.5 mm (f = 10 - 55 Hz) conforming to IEC 60068-2-6
Shock resistance	30 gn, duration 11 ms conforming to IEC 60068-2-27
IP degree of protection	IP65 double insulation conforming to IEC 60529 IP67 double insulation conforming to IEC 60529

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Schneider Electric:](#)

[XUB1BNANL2](#)