Product data sheet Characteristics

XVBC21

Ø 70 mm base unit + cover - black



Main

Mani	
Range of product	Harmony XVB Universal
Product or component type	Base unit with cover
Component name	XVBC
Indicator bank base type	Standard
Material	Polycarbonate cover unit Glass reinforced polyamide base unit

Complementary

Fixing mode	Direct or tube fixing	
Mounting diameter	70 mm	
Product destination	Banks without flash discharge tube unit	
Cable entry	Bottom or side entry	
Assembly style	Customer assembly, up to 5 units	
Terminals description ISO n°1	(COM-1)PW (COM-2)PW (COM-3)PW (COM-4)PW (COM-5)PW (GND)GROUND	
Product weight	0.19 kg	

Environment


LITVITOTITICITE	
Product certifications	CCC CSA C22-2 No 14 GOST UL 508
Standards	EN/IEC 60947-5-1
Protective treatment	TC
Ambient air temperature for storage	-4070 °C
NEMA degree of protection	NEMA 4X indoor UL 508

XVBC21

Indicator Bank without "Flash" Discharge Tube Unit

Dimensions

Below drawing shows the minimum configuration of the product. Select the number of stages according to the product characteristics in order



- Base unit
- (1) (2) Illuminated or audible signalling unit XVBC •••, to be ordered separately
- Cover (supplied with base unit)


Number of illuminated or audible signalling units (no "flash")	b in mm	b in in.
1	138	5.43
2	201	7.91
3	264	10.39
4	327	12.87
5	390	15.35

Product data sheet Mounting and Clearance

XVBC21

Base Unit for Indicator Banks

Panel Cut-out for Direct Fixing




Product data sheet Connections and Schema

XVBC21

Illuminated Beacon

Wiring Diagram



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Schneider Electric: XVBC21