

Basic terminal block - ZFK-RELG 7 - 2829933

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Basic termination blocks with spring-cage connection for NS 35/7.5 DIN rail, with end cover, for ST-REL..., ST-OV... and ST-OE... plugs, 7-pos.

The figure shows versions with a different no. of positions



Key Commercial Data

Packing unit	5 pc
GTIN	4 017918 101183
GTIN	4017918101183

Technical data

Dimensions

Width	45.6 mm
Height	58.4 mm
Depth	108 mm

General

Number of positions	7
Nominal voltage U _N	400 V (voltage is determined by the coupling connector.)
Nominal current I _N	16 A (current is determined by the coupling connector.)
Color	gray
Insulating material	PA

Connection data

Conductor cross section solid min.	0.5 mm ²
Conductor cross section solid max.	6 mm ²
Conductor cross section flexible min.	0.4 mm²
Conductor cross section flexible max.	4 mm²
Conductor cross section AWG min.	24



Basic terminal block - ZFK-RELG 7 - 2829933

Technical data

Connection data


Conductor cross section AWG max.	10
Connection method	Spring-cage connection
Stripping length	14 mm

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Drawings

Dimensional drawing



Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC RU C-DE.A*30.B.01742



Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Phoenix Contact: 2829933