

**SOT-23 PLASTIC-ENCAPSULATE
SCHOTTKY DIODE**

FEATURES

- * Power dissipation
P_D: □ 350 □ mW (T_{amb}=25°C)
- * Forward current
I_F: □ □ 100 □ mA
- * Reverse voltage
V_R: □ 30 □ V
- * Operating and storage junction temperature range
T_J, T_{stg}: -55°C to +150°C

MECHANICAL DATA



- * Case: Molded plastic
- * Epoxy: UL 94V-O rate flame retardant
- * Lead: MIL-STD-202E method 208C guaranteed
- * Mounting position: Any
- * Weight: 0.008 gram

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25 °C ambient temperature unless otherwise specified.



SOT-23



Dimensions in inches and (millimeters)

ELECTRICAL CHARACTERISTICS (@ T_A = 25°C unless otherwise noted)

CHARACTERISTICS	SYMBOL	MIN	TYP	MAX	UNITS
Reverse Breakdown Voltage (I _R =100μA)	V _(BR)	30	-	-	V
Reverse voltage leakage current (V _R =25V)	I _R	-	-	500	nA
Reverse voltage leakage current (V _R =25V, T _A = 100°C)		-	-	100	μA
Forward voltage (I _F =2mA)	V _F	-	-	0.33	V
Forward voltage (I _F =15mA)		-	-	0.45	V
Forward voltage (I _F =100mA)		-	-	1	V
Diode capacitance (V _R =0V, f=1MHz)	C _{tot}	-	-	8	pF
Reverse recovery time (I _F =I _R =10mA, I _{RR} =1.0mA, R _L =100Ω)	t _{rr}	-	-	5	ns

Marking	DB2
---------	-----

Note 1: "Fully ROHS compliant", "100% Sn plating (Pb-free)".

DISCLAIMER NOTICE

Rectron Inc reserves the right to make changes without notice to any product specification herein, to make corrections, modifications, enhancements or other changes. Rectron Inc or anyone on its behalf assumes no responsibility or liability for any errors or inaccuracies. Data sheet specifications and its information contained are intended to provide a product description only. "Typical" parameters which may be included on RECTRON data sheets and/ or specifications can and do vary in different applications and actual performance may vary over time. Rectron Inc does not assume any liability arising out of the application or use of any product or circuit.

Rectron products are not designed, intended or authorized for use in medical, life-saving implant or other applications intended for life-sustaining or other related applications where a failure or malfunction of component or circuitry may directly or indirectly cause injury or threaten a life without expressed written approval of Rectron Inc. Customers using or selling Rectron components for use in such applications do so at their own risk and shall agree to fully indemnify Rectron Inc and its subsidiaries harmless against all claims, damages and expenditures.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Rectron:](#)

[CMPSH-3C](#)