


Flexible, Flame-Retardant, General Purpose, Polyolefin Tubing

Product Facts

- 2:1 shrink ratio
- Superior abrasion and solvent resistance when compared with that of many flexible, general purpose polyolefin tubings
- Excellent physical, chemical, and electrical properties that meet or exceed industrial and military standards for highly reliable, general purpose tubing
- Flexible; conforms to irregular shapes
- Flame-retardant (colors only)
- Wide range of sizes and colors
- RoHS compliant

RNF-100



Applications

Designed to provide superior mechanical (abrasion, cut-through, and strain relief), thermal, and fluid-resistance performance in demanding environments. Widely used to provide insulation and strain relief of wire terminations and connections. Used for jacketing wire bundles and light-duty harnesses where superior abrasion resistance is a plus. Also used to identify and color-code electrical connections and wire bundles.

Installation

Minimum shrink temperature: 95°C [203°F]
Minimum full recovery temperature: 121°C [250°F]

Operating Temperature Range

-55°C to 135°C
[-67°F to 275°F]

Specifications/Approvals

Series	UL	CSA	Military	Industry	Raychem
RNF-100 Type 1 (colors)	E35586 600 V, 125°C	LR31929 600 V, 125°C	AMS-DTL-23053/5*, Class 1 Def. Stan. 59-97 Type 2B	VDE 0341 Pt 9005 Type A and B	RT-350, Type 1 RK-6001
RNF-100 Type 2 (clear)	—	—	AMS-DTL-23053/5*, Class 2 VG 95343 Pt 5 Type B	—	RT-350, Type 2 RK-6001

*Formerly MIL-I-23053/5 and MIL-DTL-23053/5.

Available in:	Americas	Europe	Asia Pacific
	■	■	■

RNF-100 (Continued)

Product Dimensions

Size	Inside Diameter		Recovered Wall Thickness**
	Minimum Expanded as Supplied	Maximum Recovered After Heating	After Heating
3/64	1.2 [0.046]	0.6 [0.023]	0.40 ± 0.08 [0.016 ± 0.003]
1/16	1.6 [0.063]	0.8 [0.031]	0.43 ± 0.08 [0.017 ± 0.003]
3/32	2.4 [0.093]	1.2 [0.046]	0.51 ± 0.08 [0.020 ± 0.003]
1/8	3.2 [0.125]	1.6 [0.062]	0.51 ± 0.08 [0.020 ± 0.003]
3/16	4.8 [0.187]	2.4 [0.093]	0.51 ± 0.08 [0.020 ± 0.003]
1/4	6.4 [0.250]	3.2 [0.125]	0.64 ± 0.08 [0.025 ± 0.003]
3/8	9.5 [0.375]	4.8 [0.187]	0.64 ± 0.08 [0.025 ± 0.003]
1/2	12.7 [0.500]	6.4 [0.250]	0.64 ± 0.08 [0.025 ± 0.003]
3/4	19.1 [0.750]	9.5 [0.375]	0.76 ± 0.08 [0.030 ± 0.003]
1	25.4 [1.000]	12.7 [0.500]	0.89 ± 0.12 [0.035 ± 0.005]
1 1/4	31.8 [1.250]	15.9 [0.625]	1.02 ± 0.15 [0.040 ± 0.006]
1 1/2	38.1 [1.500]	19.1 [0.750]	1.02 ± 0.15 [0.040 ± 0.006]
2	50.8 [2.000]	25.4 [1.000]	1.14 ± 0.16 [0.045 ± 0.007]
3	76.2 [3.000]	38.1 [1.500]	1.27 ± 0.20 [0.050 ± 0.008]
4	101.6 [4.000]	50.8 [2.000]	1.40 ± 0.23 [0.055 ± 0.009]
5	127.0 [5.000]	63.5 [2.500]	1.52 ± 0.23 [0.060 ± 0.009]

**Wall thickness will be less if tubing recovery is restricted during shrinkage.

Ordering Information

Color	Standard	Black (-0, BK), white (-9, WH), red (-2, RD), blue (-6, BU), yellow (-4, YO), clear (-X, CL)
	Nonstandard	Brown (-1, BN), orange (-3, OR), green (-5, GN), violet (-7, VT), gray (-8, GY)
Size selection	Always order the largest size that will shrink snugly over the component to be covered. Special order sizes are available upon request.	
Standard packaging***	On spools or in 1.2-meter [4-foot] lengths.	
Ordering description****	Specify product name, size and color (for example, RNF-100 1/4-0 [Europe] or RNF-100 1/4-BK [Americas]).	

***Available in the convenient Mini-Spool packaging/dispensing system, for sizes 3/64" up to 1".

****Europe only. For supply to MIL, Def Stan and BS add -MS, -DS or -BS to ordering description.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity:

[RNF-100-3/8-CL-1.5IN](#) [RNF-100-4-BK-SP-CS5004](#) [RNF-100-1-OR-FSP](#) [RNF-100-3/8-WH-SP-CS5321](#) [RNF-100-3-GN-SP](#) [RNF-100-4-CL-SP](#) [RNF-100-3/32-GY-STK](#) [RNF-100-3/8-VT-FSP-CS7807](#) [RNF-100-3/16-BN-SP](#) [RNF-100-3-0-SP](#) [RNF-100-4.5/1.9-CL-STK](#) [RNF-100-1/4-YO-SP-CS7387](#) [RNF-100-3/32-CL-SPMD/DBLBG](#) [RNF-100-3/32-BK-STK-CS5529](#) [RNF-100-3/8-WH-STK-CS5321](#) [RNF-100-1/4-RD-SP-CS7387](#) [RNF-100-1-1/2-BK-STK-CS7387](#) [RNF-100-1-9-SP](#) [RNF-100-1/8-4-SP](#) [RNF-100-1/16-WH-STK-CS5321](#) [RNF-100-3/8-4-SP](#) [RNF-100-3/32-OR-SP](#) [RNF-100-1/16-BN-SP](#) [RNF-100-3/16-4-SP](#) [RNF-100-3/16-2-SP](#) [RNF-100-3/8-BK-SP-CS7807](#) [RNF-100-1/2-RD-FSP-CS5004](#) [RNF-100-3/32-VT-SP](#) [RNF-100-3/8-CL-STK-CS7250](#) [RNF-100-1/8-CL-STK-CS8794](#) [RNF-100-3/16-BK-CSP-CS8986](#) [RNF-100-3/64-CL-STK-CS8794](#) [RNF-100-3/8-0-FSP](#) [RNF-100-NO.302-BK-SP](#) [RNF-100-3/16-VT-STK](#) [RNF-100-2-WH-STK-CS5551](#) [RNF-100-3/8-CL-FSP-CS7312](#) [RNF-100-1/8-WH-STK-CS9057](#) [RNF-100-2-GY-SP-CS5318](#) [RNF-100-3/4-BK-SP-SM](#) [RNF-100-1/16-OR-STK](#) [RNF-100-3-GN-STK](#) [RNF-100-1-1/4-0-SP](#) [RNF-100-2-4-SP](#) [RNF-100-1-1/2-GN-STK](#) [RNF-100-1/16-VT-STK](#) [RNF-100-1/16-BN-STK](#) [RNF-100-3/8-6-SP](#) [RNF-100-1/16-GY-SP](#) [RNF-100-3/32-OR-STK](#) [RNF-100-3/4-OR-STK](#) [RNF-100-3/4-BN-SP-CS5321](#) [RNF-100-0.543-BK-SP](#) [RNF-100-3-RD-STK](#) [RNF-100-1-0-FSP](#) [RNF-100-4-YO-STK](#) [RNF-100-3/8-RD-SP-CS5533](#) [RNF-100-090/105-WH-CSP](#) [RNF-100-3/8-1-FSP](#) [RNF-100-3/8-GN-SP-CS5321](#) [RNF-100-3/16-GN-SP-CS5321](#) [RNF-100-1-1/2-BN-SP](#) [RNF-100-3-BU-STK](#) [RNF-100-1-1/2-BK-SP-SM](#) [RNF-100-1-1/2-X-SP](#) [RNF-100-1/16-VT-SP](#) [RNF-100-3/16-GY-STK](#) [RNF-100-3/32-BN-SP](#) [RNF-100-3/16-6-SP](#) [RNF-100-1/2-4-SP](#) [RNF-100-1/8-BN-SP](#) [RNF-100-3/64-BK-SP-SM](#) [RNF-100-3/4-VT-SP](#) [RNF-100-4-WH-STK](#) [RNF-100-3/4-0-FSP](#)