



used for: D-SUB




(b)

Wire size AWG	Crimp height A
28	0,61 - 0,76
26	0,66 - 0,81
24	0,66 - 0,86



STRIPPING DIMENSIONS



NOTES:

Material: Phosphor Bronze

(c) Finish: Gold Flash over Nickel in the Contact Area

Temperature Range: -55°C to +125°C

Rated Current: 5.0A

Contact Resistance: <= 10mOhm

Crimping: Use Crimp Tool 360X10079X

Directive 2002/95/EC RoHS compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION.
 OWNERSHIP AND COPYRIGHT OF CONEC GmbH
 DO NOT ALTER CAD DRAWING BY HAND

				tolerance		dim. in mm
rev.	description	date	name			
				2005	date	name
				drawn	11.03.	Lehmenkühler
				appd.	11.03.	Mickenbecker
				norm		
1 x c	Ä 4116	26.09.2011	Lehmen.	d-old		
1 x b	Ä 2197	01.04.2005	HS			
a	Original					



scale:	5:1
material:	SEE NOTES
title:	PLUG CONTACT CRIMP AWG 28-24
dwg no:	16K1A1341
part no:	161A13439X

DIN-A
4
sh: 1/1

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[CONEC:](#)

[161A13439X](#)