

Sales Outline Drawing

Revision B


Specifications:

Oscillation Frequency (Hz)	1500 \pm 200
Operating Voltage (Vp-p)	2.0 \sim 5.0
Rated Voltage (Vp-p)	3.0
Input Watt (W/max)	0.15
Sound Pressure Level (dB/min)	80 at 10cm at Rated Voltage
Coil Resistance (Ω)	8.0 \pm 2
Operating Temperature (°C)	-10 \sim +40
Storage Temperature (°C)	-20 \sim +50
Housing	PPO plastic resin(Color: Black)
Lead	Tin Plated Brass
Weight (Grams)	3.2
Condition by wave soldering (°C)	245 \pm 5 / 3 \pm 0.5 sec
Condition by hand soldering (°C)	350 \pm 20 / within 5 sec
Options	White Paint Dot at Arrow


PS: Vp-p = 1/2duty, square wave

RoHS Compliant

Dimensions: (units: mm)



Recommended Driving Circuit:



The base current, I_b , should be high enough so that it saturates the collector current of the transistor with the CB load.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Mallory Sonalert:](#)

[PB-2015PAQ](#)