

# Electronic housing - EMG 25-LG - 2948319

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Electronic housing, with snap foot for DIN rail EN 50022 for PCB insertion, without screw connection terminal blocks and cover

#### Your advantages

- ☑ Practical and easy-to-wire conductor connections
- Space-saving accommodation of electronic components in finely graded module versions available with 10 to 150 mm pitch
- ☑ User-friendly and safe mounting on DIN rails according to EN 60715
- High degree of flexibility due to the wide choice of versions
- Uniform and appropriate housing technology
- ☑ Inflammability class V0 insulation material (according to UL 94)
- Shock and contamination-proof accommodation of electronic components
- Universal PCBs for all pitches



### **Key Commercial Data**

Packing unit	5 pc		
GTIN	4 017918 083267		
GTIN	4017918083267		

#### Technical data

#### General

Housing type	Component housing	
Housing material	Polycarbonate fiber reinforced	
Color (RAL)	green	

#### Ambient conditions

Ambient temperature (operation)	-40 °C 125 °C
---------------------------------	---------------

#### **Dimensions**

Length	75 mm



# Electronic housing - EMG 25-LG - 2948319

### Technical data

### Dimensions

Height	47.5 mm
Width	25 mm
Pitch	5 mm
Depth	75 mm

#### Technical data

Power dissipation without gap	1.4 W
Power dissipation with 20 mm gap	1.6 W
Number of positions	8

#### Connection data

Conductor cross section solid min.	0.2 mm²
Conductor cross section solid max.	4 mm²
Conductor cross section flexible min.	0.2 mm²
Conductor cross section flexible max.	2.5 mm²
Conductor cross section AWG min.	24
Conductor cross section AWG max.	12
Stripping length	8 mm

#### Standards and Regulations


Flammability rating according to UL 94	V0
--	----

### **Environmental Product Compliance**

China RoHS	Environmentally friendly use period: unlimited = EFUP-e	
	No hazardous substances above threshold values	

## Drawings


#### Dimensional drawing



#### Pitch 5 mm

a = Area for mounting components, 38 mm in the hood b = Area for mounting components, 45 mm in the housing

#### Dimensional drawing



- 1 = Top edge of the PCB
- B = Housing width



# Electronic housing - EMG 25-LG - 2948319

Approvais			
Approvals			
Approvals			
EAC			
Ex Approvals			
Approval details			
EAC	ERE		B.01742

Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany

Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Phoenix Contact: 2948319