

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0901361306

Status:

Active

Overview:

C-Grid III Interconnects

Description:

C-Grid III Header, Single Row, Vertical, Shrouded, 6 Circuits, 0.76µm Gold (Au)
Selective Plating

Documents:

3D Model

Packaging Specification PK-90136-001 (PDF)

Drawing (PDF)

RoHS Certificate of Compliance (PDF)

Agency Certification

CSA

LR19980

General

Product Family

Series

Application

Data Load Status

Made From

Overview

Product Name

UPC

PCB Headers

90136

Signal, Wire-to-Board

Post Go-Live Rev. Not Verified

0901262032, 0901360006

C-Grid III Interconnects

C-Grid III

800753672222

Physical

Breakaway

Circuits (Loaded)

Circuits (maximum)

Color - Resin

First Mate / Last Break

Flammability

Glow-Wire Capable

Guide to Mating Part

Keying to Mating Part

Lock to Mating Part

Material - Metal

Material - Plating Mating

Material - Plating Termination

Material - Resin

Net Weight

Number of Rows

Orientation

PC Tail Length

PCB Locator

PCB Retention

PCB Thickness - Recommended

Packaging Type

Pitch - Mating Interface

Pitch - Termination Interface

Plating min - Mating

Plating min - Termination

Polarized to PCB

Shrouded

Stackable

Temperature Range - Operating

Termination Interface: Style

No

6

6

Black

No

94V-0

No

No

None

Yes

Brass

Gold

Tin

Polyester

1.012/g

1

Vertical

2.90mm

No

None

1.60mm

Tray

2.54mm

2.54mm

0.762µm

3.048µm

No


Fully

No

-55°C to +125°C

Through Hole

Electrical



Series image - Reference only

EU ELV

Not Relevant

EU RoHS

China RoHS

Compliant

REACH SVHC

Not Contained Per

-ED/01/2018 (15

January 2018)

Halogen-Free

Status

Not Low-Halogen

Need more information on product environmental compliance?

Email productcompliance@molex.com
Please visit the [Contact Us](#) section for any non-product compliance questions.

China ROHS

Green Image

ELV

Not Relevant

RoHS Phthalates

Not Contained

Search Parts in this Series

90136 Series

Mates With

90123 C-Grid III Modular Crimp Housing,

90156 C-Grid III Crimp Housing

Current - Maximum per Contact3.0A

Voltage - Maximum350V AC/DC

Material Info

Reference - Drawing Numbers

Packaging SpecificationPK-90136-001

Sales DrawingSDA-90136

This document was generated on 02/27/2018

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Molex:

90136-1306