


COIL: @ 25°C  
 RESISTANCE 850 OHMS ± 10%  
 NOMINAL VOLTAGE 12.0 VDC  
 MUST OPERATE 7.0 VDC  
 MUST RELEASE 4.0 VDC MAX, 0.64 VDC MIN.

**CUSTOMER DATA SHEET**



ENVIRONMENT:  
 VIBRATION 10 CPS TO 3000 CPS @ 30 g's  
 SHOCK 75 g's 6 MS. DURATION  
 TEMPERATURE -65 °C TO +125 °C

CONTACT RATING: LOW LEVEL TO 1A  
28 VDC RESISTIVE 100,000 OPERATIONS

NOTES: OPERATE TIME 4 MS MAX  
RELEASE TIME 2.0 MS MAX  
CONTACT STABILIZATION TIME 2.0 MS MAX

DR. R.B. 2/24/97 *CK/eray* 12/16/97

**COMMUNICATIONS INSTRUMENTS, INC.**

CUST. OPL  
 CUST. NO. M39016/11-021M

TYPE "JMS" RELAY

**JMSW-12XM**

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[JMSW-12XM](#)