



- Notes:**
- Material:
 - (c) (b) - Protective Cap: Polyester (Black); UL94 V-0
 - Tether: Polycarbonate (Black)
 - Operating Temperature: -40°C to +85°C
 - (d) 3. IP67/IP68 rated when fully mated with the appropriate mating connector

RoHS Compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY MANNER WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC CORPORATION.	Customer:				Tolerance Unless otherwise specified			Scale: 1.5:1	Dim. in mm	
	Name		Title	Approval Date	(d)	0 PLC ±0.50		Autodesk Inventor	Material: See Notes	
	f	1 x f	Oct/10/2017	Vincent Ke	Draw.	1 PLC ±0.38	Title: Protective cap Assembly for			
	e	2 x e	Dec/09/2015	Vincent Ke	Appd.	2 PLC ±0.25	(f) IP67 Duplex LC, IP67 RJ45,			
d	1 x d	Feb/25/2013	Vincent Ke	Norm	3 PLC ±0.10	IP67 USB and IP67 Power Connectors				
c	1 x c	Feb/25/2011	Vincent Ke	D-old	ANGLES ±.7	Drawing No.: 17K1A004		DIN A3		
b	1 x b	Jun/03/2010	Vincent ke			Part No.: 17-300050		Sheet 1/1		
a	original									
Rev.	Changes	Date	Name							



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[CONEC:](#)

[17-300050](#)