

f	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6								
e	6	5	5	5	5	5	5	6	5	5	5	5	6	5	5	5	5	5	6	5	5	5	5	6							
d	6	5	5	5	5	5	5	6	5	5	5	5	6	5	5	5	5	5	6	5	5	5	5	6							
c	6	5	5	5	5	5	5	6	5	5	5	5	6	5	5	5	5	5	6	5	5	5	5	6							
b	6	5	5	5	5	5	5	6	5	5	5	5	6	5	5	5	5	5	6	5	5	5	5	6							
a	6	5	5	5	5	5	5	6	5	5	5	5	6	5	5	5	5	5	6	5	5	5	5	6							
z	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0							
P	0						0						1						1						2						2
O	1						5						0						5						0						5
S																															

Technical drawings of a component, showing front and top views with dimensions and callouts.

Front View (Left):

- Overall height: $15.40^{+0}_{-0.5}$
- Central section height: 11.70 ± 0.10 (NOTE 3)
- Top section height: $3.00^{+0}_{-0.10}$
- Bottom section height: $13.45^{+0.15}_{-0.10}$
- Callout NOTE 6 points to the central section.

Top View (Right):

- Overall length: 50.00 MAX
- Overall width: $48.00 (24 \times 2)$
- Callout NOTE 5 points to a dashed rectangular area.

Technical drawing showing two connector types, 5 and 6, with dimensions and a seating plane.

Connector 5 dimensions:

- Overall length: 9.70
- Distance from end to connector body: 3.70

Connector 6 dimensions:

- Overall length: 11.20
- Distance from end to connector body: 3.70

A vertical line indicates the SEATING PLANE FOR CONNECTOR.

A diagram of a rectangular perforated plate. The plate is 48.00 units wide and 10.00 units high. It features a grid of circular holes. The holes are arranged in 10 rows and 48 columns. The spacing between the holes is 1.00 unit in both the horizontal and vertical directions. The plate is shown with a top view, with dimension lines indicating the overall width and height.

PLATING CODE (DIGIT 13 AND 14)
(REF DRW NO. BS,C , 201844 , 003)

1. THIS PRODUCT IS CSA APPROVED.
2. THIS PRODUCT IS UL RECOGNIZED.
3. MEASURED AT THE BOTTOM.
4. MATERIAL CONTACT: PHOSPHORBRONZE
HOUSING: CREAM WHITE GLASS FILLED POLYESTER UL-94V0
5. CONNECTOR PRINTED WITH P/N AND DATE CODE.
6. FOR ACTUAL CONTACT LOADINGS, SEE LOADING PATTERN MATING SIDE.
7. SHAPE OF CONNECTOR HOUSING CAN ALTER DEPENDING ON
PRODUCTION LOCATION
8. THIS PRODUCT (LF) MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY
REGULATIONS AS DESCRIBED IN GS-22-008
9. FOR RECOMMENDED PTH DIMENSIONS REFER DRAWING : BS, A , 201572 , 001

PART NO: HM2PN2PDP2K5----

[illegible]

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[FCI / Amphenol:](#)

[HM2PN2PDP2K5N9LF](#)