



- KEYS INSTALLED IN POSITIONS AS SHOWN IN TABLE.
 - CONTACTS ARE INCLUDED IN A CONTAINER WITHIN THE CONNECTOR PACKAGE FOR SHIPMENT.
 - ALL DIMENSIONS CONFORM TO MIL-C-81659 WITH EXCEPTION TO EMI SPRING FINGERS.
 - COAX/TRIAX CONTACTS TO BE PURCHASED SEPARATELY.
 - CONFORMS TO REQUIREMENTS OF MCDONNELL DOUGLAS 5M1972.
- △ CONNECTOR VIEW AND INSERT LAYOUT IS SHOWN FOR 449583-1.
 △ MATING FACE SHOWN FOR REFERENCE ONLY.

PART NUMBER	CUSTOMER PART NUMBER	POLARIZING POSITION	MOD A	MOD B
449583-1	5M1972-01P02P	04	106P	36C7P
449583-2	5M1972-01P01P	04	106P	106P
449583-3	5M1972-01P03S	02	106P	32C2
449583-4	5M1972-04P01P	45	25C15	106P
449583-5	5M1972-02P01P	01	36C7P	106P
449583-6	5M1972-02P01PA	01	36C7P	106P

OBSELETE

THIS DRAWING IS A CONTROLLED DOCUMENT.		DIN T. ALEXANDER 4-17-96	STE TE Connectivity
DIMENSIONS: INCHES		CHK K. GUARAGNO 4-22-96	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD K. GUARAGNO 4-22-96	NAME
0 PLC ± -		ARINC 404 KIT, MME2P106P36C7P-0004 (204) WITH EMI FINGERS	
1 PLC ± -		APPLICATION SPEC	
2 PLC ± -		SIZE	
3 PLC ± .010 [0.25]		CAGE CODE	
4 PLC ± .0050		DRAWING NO	
ANGLES ± -		WEIGHT	
FINISH SEE CALLOUTS		A1 00779 C=449583	
MATERIAL SEE CALLOUTS		CUSTOMER DRAWING	
		SCALE 2:1 SHEET 1 OF 1 REV E	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[449583-5](#)