

Ferrule - AI 1 - 8 RD -1000 - 3200904

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Ferrule, Sleeve length: 8 mm, Length: 14 mm, Color: red

The figure shows the version AI 1-8
RD

Product Features

- The ferrules with plastic sleeve are made from soft tin-plated electrolytic copper
- The insulation reliability of close connections is increased and the splicing of wires is prevented
- The AI 0,25.. ferrules can also be used to process 0.14 mm² conductors



Key Commercial Data

| | |
|--------------------------------------|---|
| Packing unit | 1 pc |
| Minimum order quantity | 1000 pc |
| GTIN |  4 017918 094454 |
| Weight per Piece (excluding packing) | 0.1066 g |
| Custom tariff number | 85369010 |
| Country of origin | Germany |

Technical data

Dimensions

| | |
|--|--------|
| Length (b) | 14 mm |
| Maximum stripping length | 11 mm |
| Sleeve length | 8 mm |
| Inner dimension of the insulating collar (d) | 3 mm |
| Ferrule diameter | 1.5 mm |
| Insulating collar thickness | 0.3 mm |

Ferrule - AI 1 - 8 RD -1000 - 3200904

Technical data

Dimensions

| | |
|-----------------------|---------|
| Sleeve wall thickness | 0.15 mm |
|-----------------------|---------|

Ambient conditions

| | |
|----------------------------|--------|
| Short-term temperature | 120 °C |
| Max. permanent temperature | 105 °C |

General

| | |
|--|--------------------------------|
| Color | red |
| Components | free from silicone and halogen |
| Flammability rating according to UL 94 | HB |
| Material | E-CU |
| Coating | tin-plated (galvanic) |

Standards and Regulations

| | |
|--|-----|
| Connection in acc. with standard | CSA |
| Flammability rating according to UL 94 | HB |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 27060701 |
| eCl@ss 4.1 | 27060701 |
| eCl@ss 5.0 | 27400201 |
| eCl@ss 5.1 | 27400201 |
| eCl@ss 6.0 | 27400201 |
| eCl@ss 7.0 | 27400201 |
| eCl@ss 8.0 | 27400201 |

ETIM

| | |
|----------|----------|
| ETIM 2.0 | EC000005 |
| ETIM 3.0 | EC000005 |
| ETIM 4.0 | EC000005 |
| ETIM 5.0 | EC000005 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 30212109 |
| UNSPSC 7.0901 | 27121703 |
| UNSPSC 11 | 27121703 |
| UNSPSC 12.01 | 27121703 |

Ferrule - AI 1 - 8 RD -1000 - 3200904

Classifications

UNSPSC

| | |
|-------------|----------|
| UNSPSC 13.2 | 27121703 |
|-------------|----------|

Approvals

Approvals

Approvals

CSA / CSAus / EAC / EAC / cCSAus

Ex Approvals

Approvals submitted

Approval details

| |
|---|
| CSA  |
|---|

| |
|-------|
| CSAus |
|-------|

| |
|-----|
| EAC |
|-----|


| |
|-----|
| EAC |
|-----|

| |
|--------|
| cCSAus |
|--------|

Drawings

Ferrule - AI 1 - 8 RD -1000 - 3200904

Dimensional drawing



Phoenix Contact 2016 © - all rights reserved
<http://www.phoenixcontact.com>

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Phoenix Contact:](#)

[3200904](#)