


CUI INC
date 10/2010

page 1 of 3

SERIES: ACZ11

DESCRIPTION: mechanical incremental encoder

ELECTRICAL SPECIFICATIONS

parameter	conditions/description
output waveform	square wave
output signals	A, B phase
current consumption	10 mA
output phase difference	T1, T2, T3, T4 $\geq$ 3.5 ms @ 60 rpm (see output waveform)
supply voltage	5 V dc max.
output resolution	12, 15, 20, 30 ppr
switch rating	12 V dc, 50 mA (ACZ11BRXE models only)
insulation resistance	300 V dc, 100 M Ω
withstand voltage	300 V ac


MECHANICAL SPECIFICATIONS

parameter	conditions/description	min	nom	max	units
shaft load	axial			8	kgf
rotational torque	with detent click	60	140	220	gf·cm
	without detent click	60	80	100	gf·cm
push switch operational force	(ACZ11BRXE models only)	300		900	gf·cm
push switch life	(ACZ11BRXE models only)			50,000	cycles
rotational life				30,000	cycles

ENVIRONMENTAL SPECIFICATIONS

parameter	conditions/description	min	nom	max	units
operating temperature		-10		65	°C
storage temperature		-40		75	°C
humidity		85			% RH
vibration	0.75 mm max. travel for 2 hours	10		55	Hz

PART NUMBER KEY





CUI INC
date 10/2010

page 2 of 3

SERIES: ACZ11

DESCRIPTION: mechanical incremental encoder

SHAFT OPTIONS



switch travel for ACZ11BRXE only

BUSHING

	Condition	H
1	M7-P0.75	5
2	M7-P0.75	7
4	smooth	5
5	smooth	7

H=5	15KQ	20KQ	25KQ
L	15	20	25
I	7	10	12

H=7	15KQ	20KQ	25KQ
L	15	20	25
I	5	8.5	10


H=5	15S	20S	25S
L	15	20	25

H=7	15S	20S	25S
L	15	20	25

H=5	15F	20F	25F
L	15	20	25
F	8	12	12

H=7	15F	20F	25F
L	15	20	25
F	8	12	12


OUTPUT WAVEFORM



CW direction (@ 60 rpm)


DETENT POSITIONS

Model 12C & 20C




CW direction →

Model 15P30C




CW direction →

SLIDING NOISE

 $t = \text{Masking time to avoid chatter (5mS)}$ $V_1 = V_2 = 1V \text{ max.}$


SUGGESTED FILTER


 $R1, R2, R3, R4 = 10k\Omega$
 $C1, C2 = 0.01\mu F$



CUI INC

date 10/2010



page 3 of 3

SERIES: ACZ11


DESCRIPTION: mechanical incremental encoder

MECHANICAL DRAWING (horizontal)


ACZ11NBRXE





PANEL CUT-OUT




PCB LAYOUT




ACZ11BRXE



PANEL CUT-OUT





PCB LAYOUT




MECHANICAL DRAWING (vertical)


ACZ11NBRXE





PANEL CUT-OUT




PCB LAYOUT




ACZ11BRXE



PANEL CUT-OUT



PCB LAYOUT



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

CUI Inc.:

[ACZ11BR1E-15FD1-20C](#) [ACZ11BR1E-15FD1-12C](#) [ACZ11BR1E-20KQD1-20C](#) [ACZ11BR1E-15FA1-12C](#)
[ACZ11BR1E-15KQD1-12C](#) [ACZ11BR1E-15KQD1-20C](#) [ACZ11BR1E-20FD1-20C](#) [ACZ11BR1E-20FD1-12C](#)
[ACZ11BR1E-20KQD1-12C](#) [ACZ11BR1E-20FA1-12C](#) [ACZ11BR1E-20FA1-20C](#) [ACZ11BR1E-15FA1-20C](#)
[ACZ11BR1E-15KQA1-12C](#) [ACZ11BR1E-15KQA1-20C](#) [ACZ11BR1E-20KQA1-12C](#) [ACZ11BR1E-20KQA1-20C](#)
[ACZ11BR4E-15FA1-12C](#) [ACZ11BR4E-15FA1-20C](#) [ACZ11BR4E-20FD1-12C](#) [ACZ11BR4E-20FD1-20C](#) [ACZ11BR4E-20KQD1-12C](#) [ACZ11BR4E-20KQD1-20C](#) [ACZ11BR4E-15FD1-12C](#) [ACZ11BR4E-15FD1-20C](#) [ACZ11BR4E-15KQD1-12C](#) [ACZ11BR4E-15KQD1-20C](#) [ACZ11BR4E-20FA1-12C](#) [ACZ11BR4E-20FA1-20C](#)