

## Heavy Duty Fuse Clip, 6.3x32 mm, 600 VAC/VDC, 32 A





Solder THT version tin-plated

Solder THT version silver-plated

## 600 VAC/DC · 32 A (UL)

#### See below:

### **Approvals and Compliances**

#### **Description**

- Solder mounting

## **Unique Selling Proposition**

- Unique 600 VAC/VDC and 32 A
- Minimal power loss due to strong clamping force

#### **Applications**

- Photovoltaic
- Applications for high currents and voltages
- Equipment with three-phase supply (400 VAC)

#### References

Fuseholder to A12FA 660V; FSF 6.3x32; FST 6.3x32; SA 6.3x32; SHF 6.3x32; SHT 6.3x32; SP 6.3x32; SPT 6.3x32; SUT 6.3x32

#### Weblinks

pdf data sheet, html datasheet, General Product Information, Packaging details, Distributor-Stock-Check, Detailed request for product, Microsite

#### **Technical Data**

6.3 x 32 mm
PCB
Solder THT
600 VAC/DC
32 A (UL)
-55 °C to 155 °C 1)
Copper alloy, silver-plated / tin-plated 1)
0°C to 60°C, max. 70% r.h.

Soldering Methods	Wave
	Soldering Profile
Solderability	245°C / 3 sec acc. to IEC 60068-2-20,
	Test Ta, method 1
Resistance to Soldering Heat	260°C / 10 sec acc. to IEC 60068-2-20,
	Test Tb, method 1A
Contact Resistance	≤ 10 mΩ at 100 mA

## **Approvals and Compliances**

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in Details about Approvals

SCHURTER products are designed for use in industrial environments. They have approvals from independent testing bodies according to national and international standards. Products with specific characteristics and requirements such as required in the automotive sector according to IATF 16949, medical technology according to ISO 13485 or in the aerospace industry can be offered exclusively with customer-specific, individual agreements by SCHURTER.

## **Approvals**

The approval mark is used by the testing authorities to certify compliance with the safety requirements placed on electronic products. Approval Reference Type: CQP

Approval Logo	Certificates	Certification Body	Description
c <b>FL</b> °us	UL Approvals	UL	UL File Number: E39328

## **Product standards**

Product standards that are referenced

Organization	Design	Standard	Description
(UL)	Designed according to	UL 4248-1	Fuseholder general requirements
CSA Group	Designed according to	CSA C22.2 no. 4248.1	Fuseholder general requirements

<sup>1)</sup> Details see table of variants

## **Application standards**

Application standards where the product can be used

Organization	Design	Standard	Description
<u>IEC</u>	Designed for applications acc.	IEC/UL 60950	IEC 60950-1 includes the basic requirements for the safety of information technology equipment.


#### Compliances


The product complies with following Guide Lines

duct complies with the applicable isation of Community legislation on ulation 765/2008.
ent (EU) 2015/863
HS) has been in force since 1 March loHS.
907/2006 on the Registration, on of Chemicals 1 (abbreviated as
1

## Dimension [mm]

┥8.2 mm





Drilling diagram

### **All Variants**

Clip	ip Material: Anschlüsse Order Numl		_
•	Tin-plated	8040.0001	
•	silver-plated	8040.0003	

Most Popular.

Availability for all products can be searched realtime:https://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER

Bulk (1000 pcs.) **Packaging Unit** 

**Circuit Protection** 

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Schurter:

8040.0001 8040.0003