


## Feed-through header - MC 1,5/ 7-GF-3,81 AU - 1892958

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid  
(<http://phoenixcontact.com/download>)


PCB headers, nominal current: 8 A, rated voltage (III/2): 160 V, number of positions: 7, pitch: 3.81 mm, color: green, contact surface: Gold, mounting: Wave soldering



The figure shows a 10-position version of the product

### Your advantages

- ✓ Gold-plated contacts ensure transfer quality remains stable over the long term
- ✓ Well-known mounting principle allows worldwide use
- ✓ Screwable flange for superior mechanical stability
- ✓ Maximum flexibility when it comes to device design – one header for connectors with different connection technologies



### Key Commercial Data

|              |                                                                                                         |
|--------------|---------------------------------------------------------------------------------------------------------|
| Packing unit | 50 pc                                                                                                   |
| GTIN         | <br>4 017918 382476 |
| GTIN         | 4017918382476                                                                                           |

### Technical data

#### Dimensions

|                          |              |
|--------------------------|--------------|
| Length [ l ]             | 9.2 mm       |
| Width                    | 37.06 mm     |
| Pitch                    | 3.81 mm      |
| Dimension a              | 22.86 mm     |
| Width [ w ]              | 37.06 mm     |
| Height [ h ]             | 10.3 mm      |
| Height                   | 6.9 mm       |
| Length of the solder pin | 3.4 mm       |
| Pin dimensions           | 0.8 x 0.8 mm |
| Length                   | 9.2 mm       |

#### General

# Feed-through header - MC 1,5/ 7-GF-3,81 AU - 1892958

## Technical data

### General

|                                        |               |
|----------------------------------------|---------------|
| Range of articles                      | MC 1,5/...-GF |
| Insulating material group              | IIIa          |
| Rated surge voltage (III/3)            | 2.5 kV        |
| Rated surge voltage (III/2)            | 2.5 kV        |
| Rated surge voltage (II/2)             | 2.5 kV        |
| Rated voltage (III/3)                  | 160 V         |
| Rated voltage (III/2)                  | 160 V         |
| Rated voltage (II/2)                   | 250 V         |
| Connection in acc. with standard       | EN-VDE        |
| Nominal current $I_N$                  | 8 A           |
| Maximum load current                   | 8 A           |
| Insulating material                    | PBT           |
| Flammability rating according to UL 94 | V0            |
| Color                                  | green         |
| Number of positions                    | 7             |

### Standards and Regulations

|                                        |        |
|----------------------------------------|--------|
| Connection in acc. with standard       | EN-VDE |
|                                        | CSA    |
| Flammability rating according to UL 94 | V0     |

### Environmental Product Compliance

|            |                                                                                                     |
|------------|-----------------------------------------------------------------------------------------------------|
| REACH SVHC | Lead 7439-92-1                                                                                      |
| China RoHS | Environmentally Friendly Use Period = 50                                                            |
|            | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

## Approvals

### Approvals

#### Approvals

CSA / IECEx CB Scheme / VDE Gutachten mit Fertigungsüberwachung / EAC / cULus Recognized

#### Ex Approvals

### Approval details

## Feed-through header - MC 1,5/ 7-GF-3,81 AU - 1892958

### Approvals

|                    |                                                                                   |                                                                                                                                         |       |
|--------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|-------|
| CSA                |  | <a href="http://www.csagroup.org/services-industries/product-listing/">http://www.csagroup.org/services-industries/product-listing/</a> | 13631 |
|                    | D                                                                                 | B                                                                                                                                       |       |
| Nominal voltage UN | 300 V                                                                             | 300 V                                                                                                                                   |       |
| Nominal current IN | 8 A                                                                               | 8 A                                                                                                                                     |       |

|                    |                                                                                   |                                                           |                |
|--------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------|----------------|
| IECEE CB Scheme    |  | <a href="http://www.iecee.org/">http://www.iecee.org/</a> | DE1-60987-B1B2 |
|                    |                                                                                   |                                                           |                |
| Nominal voltage UN | 160 V                                                                             |                                                           |                |
| Nominal current IN | 8 A                                                                               |                                                           |                |

|                                            |                                                                                    |                                                                                                                                                                                                                |          |
|--------------------------------------------|------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|
| VDE Gutachten mit<br>Fertigungsüberwachung |  | <a href="http://www2.vde.com/de/Institut/Online-Service/VDE-gepruefteProdukte/Seiten/Online-Suche.aspx">http://www2.vde.com/de/Institut/Online-Service/<br/>VDE-gepruefteProdukte/Seiten/Online-Suche.aspx</a> | 40011723 |
|                                            |                                                                                    |                                                                                                                                                                                                                |          |
| Nominal voltage UN                         | 160 V                                                                              |                                                                                                                                                                                                                |          |
| Nominal current IN                         | 8 A                                                                                |                                                                                                                                                                                                                |          |

|     |                                                                                     |  |         |
|-----|-------------------------------------------------------------------------------------|--|---------|
| EAC |  |  | B.01742 |
|-----|-------------------------------------------------------------------------------------|--|---------|

|                    |                                                                                     |                                                                                                                                                       |                 |
|--------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| cULus Recognized   |  | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> | E60425-20110128 |
|                    | D                                                                                   | B                                                                                                                                                     |                 |
| Nominal voltage UN | 300 V                                                                               | 300 V                                                                                                                                                 |                 |
| Nominal current IN | 8 A                                                                                 | 8 A                                                                                                                                                   |                 |

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Phoenix Contact:](#)

[1892958](#)