
XZCP1340L5

pre-wired connectors XZ - elbowed female -M12 - 3 pins - cable PUR 5m

Product availability: Non-Stock - Not normally stocked in distribution facility Price*: 30.10 USD



Main	
Commercial Status	Commercialised
Accessory / separate part category	Cabling accessories
Accessory / separate part type	Pre-wired connectors
Series name	General purpose
Electrical connection	Elbowed female connector M12, 3 pins
Collar material	Metal
Status LED	2 PNP LEDs
Cable length	16.4 ft (5 m)

Comp	alen	ent	arv/
COILL		Citt	aiy

Cable connector fixing	Screw-on	
Cable outer diameter	0.2 in (5.2 mm)	
Cable composition	3 x 0.34 mm ²	
Wire insulation material	PUR	
[Ue] rated operational voltage	1030 V DC	
[In] rated current	4 A	
Contact resistance	<= 5000 μOhm	
Insulating resistance	>= 1 GΩ	
Product weight	0.4 lb(US) (0.18 kg)	

Environment

IP degree of protection	IP67	
Ambient air temperature for operation	23176 °F (-580 °C) (flexing) -40176 °F (-4080 °C) (static)	
Ambient air temperature for storage	-40176 °F (-4080 °C)	

Ordering and shipping details

Category	22483 - MACHINE CABLES	
Discount Schedule	DS3	
GTIN	00785901642299	
Nbr. of units in pkg.	1	
Package weight(Lbs)	0.33	
Product availability	Non-Stock - Not normally stocked in distribution facility	
Returnability	Υ	
Country of origin	PL	

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Compliant - since 0649 - Schneider Electric declaration of conformity

Contractual warranty

Contra	Contractual warranty	
Period		18 months

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Schneider Electric: XZCP1340L5