



PART NO.	
FILTER	CAPACITANCE
TYPE 1	180pF±20%
TYPE 3	370pF±20%
TYPE 4	830pF±20%

NOTES:

1. RoHS COMPLIANT
2. METAL SHELLS: STEEL; min. 315µin TIN over 40-80µin NICKEL
3. INSULATORS: PBT GF UL 94 V-0, BLACK
4. CONTACTS: COPPER ALLOY
5. THREADED INSERT: COPPER ALLOY; min. 200µin TIN over 80µin NICKEL
6. ADAPTER SCREW: COPPER ALLOY; NICKEL PLATED
7. CAPACITANCE: SEE TABLE
8. DIELECTRIC WITHSTANDING VOLTAGE: 300 VDC
9. MAXIMUM TORQUE VALUE FOR THREAD: 6 in.lB
10. CONNECTOR IS PART MARKED: [PART-NO.] CONEC [ABC]

tolerance		scale: 2:1 (5:1)		material: SEE NOTES	
1997		date		name	
drawn		28.01.		Barcinski	
appd.		28.01.		Mickenbecker	
norm					
d-old					
rev.		description		date	
a		Origin			
THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GMBH DO NOT ALTER CAD DRAWING BY HAND					
title: HD FILTER ADAPTER 62 polig					
dwg no: 24K11Q0A					
REL.13 DIN-A 3 sh. 1/1					
product no: SEE TABLE					

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[CONEC:](#)

[243A11670X](#)