	REV.	DATE	DESCRIPTION
	A	06/05/03	UPDATE DRAWING FORMAT
4.00 [.158] RECOMMENDED CABLE STRIPPING DIM'S			
STAMP (IF ANY) 12.00 12.40 1.488]			
6 10020WILC FOR MEDINEERS ARE 5 0.5 - 8 mm ± 0.20 mm 6 0.5 - 8 mm ± 0.40 mm	DATE 06/05/0	D3 PART DESCR	BNC CRIMP PLUG
			(FOR 734A CABLE)
4 FERRULE COPPER NICKEL 1 UNLESS OTHERWISE SPECIFIED			
4 FERRULE COPPER NICKEL 1 Issues Issues 3 INSULATOR TEFLON NATURAL 1 UNLESS OTHERWISE SPECIFIED SHEET 1_OF_1			
4 FERRULE COPPER NICKEL 1 3 INSULATOR TEFLON NATURAL 1 2 CONTACT PIN BRASS GOLD 1 .020315 = ± 0.007 .315 - 1.180 = ± 0.015" .315 - 1.06" .315 - 1.06"		PART NO.	· · ·
4 FERRULE COPPER NICKEL 1 3 INSULATOR TEFLON NATURAL 1 2 CONTACT PIN BRASS GOLD 1		PART NO.	112951 112951.DWG REV. A SIZE A SCALE NA

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Amphenol: <u>112951</u>