

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

| LOC | | DIST | | REVISIONS | | | |
|-----|-----|---------------------------|---------|-----------|------|--|--|
| P | LTR | DESCRIPTION | DATE | DWN | APVD | | |
| | A2 | REVISED PER ECO-13-000800 | 16JAN12 | KH | PO | | |

WHITE INDICATOR LINE
 SPUN ALUMINUM INLAY
 103±1
 PKES140B AND PKES150B ONLY
 (SEE SPECIFICATIONS)
 ∅ A
 SEE NOTE 6
 #6-32 UNC-2B
 SET SCREW HOLE
 ∅ B ∅ C ∅ D
 E
 F
 G
 H

SPECIFICATIONS:

MATERIAL: PHENOLIC , COLOR: BLACK.
 SHAFT HOLE INSERT: COPPER ALLOY.
 SET SCREW: #6-32 UNC-2A
 PKES60B, PKES70B, PKES90B, AND PKES120B
 ONE SET SCREW ONLY.
 PKES140B AND PKES150B, TWO SET SCREWS ONLY.

NOTES:

- INTERPRET DRAWING PER ASME Y14.5M-1994.
- DECORATIVE SPUN ALUMINUM INLAY.
- PLASTIC OVERLAY MUST BE PRESENT ON TOP SURFACE.
- PACKAGING: FOR P/N PKES140B-1/4 & PKES120B-1/4, A CARDBOARD SHEET SHALL BE INSERTED BETWEEN THE OUTER SLEEVE & KNOB TRAY SO AS TO PREVENT THE KNOBS FROM FALLING OUT OF THEIR RESPECTIVE POCKETS.
- VOID CORING FROM BOTTOM SIDE OF KNOB OPTIONAL.
- DIMENSIONS DO NOT APPLY IN MOLD GATE AREA.

5

| P/N | MODEL | SHAFT HOLE ∅ | "A" | "B" | "C" | "D" | "E" | "F" | "G" | "H" |
|-------------|-------------|--------------|-------|-------|-------|-------|------|------|------|------|
| 5-1437624-1 | PKES60B1/8 | .126 | .748 | .618 | .400 | .460 | .090 | .220 | .370 | .470 |
| 5-1437624-0 | PKES60B1/4 | .251 | .748 | .618 | .400 | .460 | .090 | .220 | .370 | .470 |
| 5-1437624-2 | PKES70B1/4 | | .855 | .744 | .508 | .705 | .080 | .275 | .421 | .526 |
| 5-1437624-3 | PKES90B1/4 | | 1.012 | .889 | .623 | .846 | .079 | .256 | .500 | .570 |
| 4-1437624-6 | PKES120B1/4 | | 1.296 | 1.160 | .858 | 1.018 | .118 | .320 | .500 | .628 |
| 4-1437624-7 | PKES140B1/4 | | 1.500 | 1.374 | 1.094 | 1.217 | .118 | .280 | .540 | .693 |
| 4-1437624-8 | PKES150B1/4 | | 1.768 | 1.551 | 1.217 | 1.413 | .118 | .300 | .733 | .831 |

| TOLERANCE CHART | | |
|-----------------|-----------|------------------|
| | DIMENSION | TOLERANCE |
| SHAFT HOLE | .126 DIA. | + .003 - .000 |
| | .251 DIA. | + .003 - .000 |

WAS DWG 80444

| | | | | | |
|---|--|-----------------------|-----------------|----------------------------|--------------------|
| THIS DRAWING IS A CONTROLLED DOCUMENT. | | DWN BSV | 14JUL04 | STE TE Connectivity | |
| DIMENSIONS: INCHES | | CHK - | APVD M ZITTO | | |
| TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± .015 4 PLC ± - ANGLES ± 2° | | APPLICATION SPEC - | | SIZE A2 | CAGE CODE 00779 |
| MATERIAL SEE SPECIFICATIONS | | WEIGHT - | | DRAWING NO 4-1437624-6 | RESTRICTED TO - |
| CUSTOMER DRAWING | | | | SCALE 1:1 | SHEET 1 of 1 |
| | | | | REV A2 | |

1471-9 (3/11)

4-1437624-6

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[PKES140B1/4](#)