



Micro Commercial Components

Micro Commercial Components 130 W Cochran St, Unit B Simi Valley, CA 93065 Tel:818-701-4933

1N5400 THRU 1N5408

Features

- Halogen free available upon request by adding suffix "-HF"
- Low Current Leakage and Low Forward Voltage
- Lead Free Finish/RoHS Compliant(Note 1) ("P" Suffix designates RoHS Compliant. See ordering information)
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1

Maximum Ratings

- Operating Temperature: -55°C to +150°C
- Storage Temperature: -55°C to +150°C
- Maximum Thermal Resistance; 30°C/W Junction To Lead

MCC	Device	Maximum	Maximum	Maximum
Catalog	Marking	Recurrent	RMS	DC
Number		Peak	Voltage	Blocking
		Reverse	_	Voltage
		Voltage		
1N5400	1N5400	50V	35V	50V
1N5401	1N5401	100V	70V	100V
1N5402	1N5402	200V	140V	200V
1N5404	1N5404	400V	280V	400V
1N5405	1N5405	500V	350V	500V
1N5406	1N5406	600V	420V	600V
1N5407	1N5407	V008	560V	V008
1N5408	1N5408	1000V	700V	1000V

Electrical Characteristics @ 25°C Unless Otherwise Specified


100ti 10ai oriai aotoria	= = = =		thor wise epocinion
Average Forward Current	$I_{F(AV)}$	3.0A	T _a = 105°C
Peak Forward Surge Current	I _{FSM}	200A	8.3ms, half sine
Forward Voltage	V_{F}	1.0V	I _F = 3.0A; T _a = 25°C
Maximum DC Reverse Current At Rated DC Blocking Voltage	I _R	5.0μA 100μA	T _a = 25°C T _a = 150°C
Typical Junction Capacitance	CJ	40pF	Measured at 1.0MHz, V _R =4.0V

Notes:1.High Temperature Solder Exemption Applied, see EU Directive Annex 7.

DO-201AD

3 Amp Rectifier


50 - 1000 Volts




DIMENSIONS						
	INCHES		MM			
DIM	MIN	MAX	MIN	MAX	NOTE	
Α	.287	.374	7.30	9.50		
В	.189	.208	4.80	5.30		
С	.048	.052	1.20	1.30		
D	1.000		25.40			




Figure 1 Typical Forward Characteristics



Instantaneous Forward Current - Amperes versus Instantaneous Forward Voltage - Volts



Average Forward Rectified Current - Amperesversus Ambient Temperature -°C




Junction Capacitance - pF*versus* Reverse Voltage - Volts




1N5400 thru 1N5408

Figure 4
Typical Reverse Characteristics



Instantaneous Reverse Leakage Current - MicroAmperesversus Percent Of Rated Peak Reverse Voltage - Volts



Peak Forward Surge Current - Amperesversus Number Of Cycles At 60Hz - Cycles



Ordering Information:

Device	Packing
Part Number-TP	Tape&Reel: 1.2Kpcs/Reel
Part Number-AP	Ammo Packing: 1.2Kpcs/Ammo Box
Part Number-BP	Bulk: 12Kpcs/Carton

Note: Adding "-HF" suffix for halogen free, eg. Part Number-TP-HF

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Micro Commercial Components (MCC):

1N5400-TP 1N5401-TP 1N5402-TP 1N5404-TP 1N5406-TP 1N5407-TP 1N5408-TP