



LOC	DIST	REVISIONS				
		P	LTR	DESCRIPTION	DATE	DWN APVD
AJ	16		0	REV PER EC-0S14-0496-04	31JAN2005	GA—
			01	REVISED PER ECO-09-024927	10NOV09	KK AEG



- 1 USE HAND TOOL: 354940-1
2. USE INSTRUCTION SHEET 408-4144
- 3 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI



RECOMMENDED STRIP LENGTH

3	OBSOLETE	55/U, 55A/U, 55B/U, 223/U	220189-1	—	9-329099-0	221149-6	414124-1	5414173-6			
		RG-174/U, 174A/U, 188/U, 188A/U, 316/U	220210-1	227194-1	9-328666-0	2-221149-0	414124-3	—5414173-3—			
		FOR USE WITH CABLE	DIE SET	④ TUBING QTY=1	③ FERRULE QTY=1	② CONTACT QTY=1	① PLUG ASSEMBLY QTY=1	PART NUMBER			
		THIS DRAWING IS A CONTROLLED DOCUMENT.							DWN G. ATTADIA — DOCK5	Tyco Electronics Corporation Harrisburg, PA 17105-3608	
		DIMENSIONS: INCHES		TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD —		NAME			
				0 PLC ± — 1 PLC ± — 2 PLC ± 0.41 [016] 3 PLC ± — 4 PLC ± — ANGLES ± —		PRODUCT SPEC —		PLUG, RIGHT ANGLE, 50 OHM, COMMERCIAL TNC			
		APPLICATION SPEC —		WEIGHT —		SIZE		CAGE CODE	DRAWING NO	RESTRICTED TO	
		MATERIAL —		FINISH —		A2 00779		C=5414173		—	
		CUSTOMER DRAWING					SCALE 5:1		SHEET 1 OF 1	REV 01	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[5414173-6](#)