




REF -50 OPTION SCREW
(WHERE APPLICABLE)



4 CIRCUIT SHOWN



NOTES:

1. MATERIAL: SEE TABLE
2. "XX" REFERS TO THE QUANTITY OF CIRCUITS.
3. ALL COMPONENTS ARE ROHS COMPLIANT.

5	XX	SCREW&WASHER, #6-32X.25 PAN, PH/SL (-50 OPT)	STEEL	ZINC CLEAR CHROMATE
4	XX	SCREW, #6-32X.25 BHD, PH/SL (-49 OPT)	BRASS	NICKEL
3	XX	SCREW, #6-32X.25 BHD, PH/SL (STANDARD)	STEEL	ZINC CLEAR CHROMATE
2	XX	TERMINAL, QUICK CONNECT (STYLE 9)	BRASS	TIN
1	1	INSULATOR, SR, CS, INSL BASE, MTG.	THERMOPLASTIC	BLACK
ITEM	QTY	DESCRIPTION	MATERIAL	FINISH

CORRECTION ON -50 OPT.
EC NO: ETC2007-0333
DRMNAH/DALGO 2007/04/24
CHKD: JENCINAS 2007/04/27
APPR: JMACNEIL 2007/04/30

QUALITY SYMBOLS
▽=0
▽=0

GENERAL TOLERANCES (UNLESS SPECIFIED)	
mm	INCH
4 PLACES ± ---	± ---
3 PLACES ± ---	± .005
2 PLACES ± 0.13	± .01
1 PLACE ± 0.3	± ---
ANGULAR ± 2 °	
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	

DIMENSION STYLE	
MM/IN	DATE
DRAWN BY	EHILE 2006/08/23
CHECKED BY	JMACNEIL 2006/08/23
APPROVED BY	JMACNEIL 2006/08/23
MATERIAL NO.	SEE CHART

SCALE 2:1		DESIGN UNITS INCH	 THIRD ANGLE PROJECTION
TITLE			
9.53MM [.375] SR BTS CS ASSY, INSULATED QUICK CONNECT W/MTG.			
 MOLEX INCORPORATED			
DOCUMENT NO. SD-38725-002			SHEET NO. 1 OF 2
CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX O SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION			

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Molex:

[38725-1002](#) [38725-1003](#) [38725-1008](#) [38725-1012](#) [38725-1204](#) [38725-1404](#) [38725-1405](#) [38725-1406](#) [38725-1408](#) [38725-1409](#) [38725-1410](#)