



Product: [9536](#)

RS-232, #24-6c, SR-PVC, O/A Foil, PVC Jkt, CMG

Product Description

Computer EIA RS-232 Cable, 24 AWG stranded (7x32) tinned copper conductors, semi-rigid PVC insulation, overall Beldfoil® shield (100% coverage), 24 AWG stranded tinned copper drain wire, PVC jacket.

Technical Specifications

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	No. of Conductors
24	7x32	TC - Tinned Copper	6

Conductor Count:	6
------------------	---

Insulation

Material	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.01 in

Color Chart

Number	Color
1	Black
2	White
3	Red
4	Green
5	Brown
6	Blue

Outer Shield Material

Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Alum / Poly	Beldfoil®	100 %	TC - Tinned Copper	24	7x32

Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.209 in	0.032 in

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR	Nominal Outer Shield DCR
25 Ohm/1000ft	18 Ohm/1000ft

Capacitance

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield	Nom. Capacitance Conductor to Shield
33 pF/ft	65 pF/ft	12.8 pF/m

High Frequency (Nominal/Typical)

Nom. Insertion Loss

12.7 dB/100m

Current

Max. Recommended Current [A]

1.75 Amps per conductor @ 25°C A

Current Table Note: 10C Temperature Rise

Voltage

UL Voltage Rating

300 V RMS

Temperature Range

UL Temp Rating: 80°C (UL AWM Style 2464)

Operating Temp Range: -30°C To +80°C

Mechanical Characteristics

Bulk Cable Weight: 24 lbs/1000ft

Max Recommended Pulling Tension: 33 lbs

Min Bend Radius/Minor Axis: 2.25 in

Standards

NEC Articles: 800

NEC/(UL) Specification: CMG

CEC/C(UL) Specification: CMG

UL AWM Style: 2464 (300 V 80°C)

CPR Euroclass: Eca

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2003/96/EC (BFR): Yes

EU Directive 2011/65/EU (ROHS II): Yes

EU Directive 2012/19/EU (WEEE): Yes

EU Directive Compliance: EU Directive 2003/11/EC (BFR)

EU CE Mark: Yes

EU RoHS Compliance Date (yyyy-mm-dd): 2005-04-01

MII Order #39 (China RoHS): Yes

Suitability

Suitability - Indoor: Yes

Flammability, LSOH, Toxicity Testing

UL Flammability: UL1685 FT4 Loading

CSA Flammability: FT4

ISO/IEC Flammability: IEC 60332-1-2

UL voltage rating: 300 V RMS

Plenum/Non-Plenum

Plenum (Y/N): No

Part Number

Variants

Item #	Color	UPC	Length	Footnote
9536.001525	Chrome		1,525 m	
9536.0030	Chrome		30 m	
9536.00U152	Chrome		152 m	
9536.00U305	Chrome		305 m	
9536.01152	Chrome		152 m	
9536.01305	Chrome		305 m	
9536 060100	Chrome	612825255222	100 ft	

9536 0601000	Chrome	612825255239	1,000 ft	C
9536 060500	Chrome	612825255246	500 ft	C
9536 0605000	Chrome	612825255253	5,000 ft	
9536 060U1000	Chrome	612825255208	1,000 ft	
9536 060U500	Chrome	612825255215	500 ft	
9536.K1305	Chrome		305 m	

Footnote:	C - CRATE REEL PUT-UP.
-----------	------------------------

History

Update and Revision:	Revision Number: 0.301 Revision Date: 04-02-2020
----------------------	--

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.