



FEATURES:

- Front and vertical stacking banana plug.
- Mates to standard banana jacks.
- Ideal for providing jumpers on chassis boxes

MATERIALS:

Conn: Extension Stacking Banana Plug

Material: Spring, Beryllium Copper per QQ-C-533, Berylco 25, Cond. HT.

Plug Body and Plug Jack: Brass, per QQ-B-626, Alloy 360, ½ hard.

Finish: Nickel plate per QQ-N-290 class 2 (.0002 min.).

Insulation: Polypropylene molded to plug body, plug jack and wire

Color: Matches color of wire.

Marking: "MODEL HB-XX"

Wire: 18 AWG, stranding 65 x 36 t.c., PVC insulated (.050 wall thickness).

Color: See Ordering Information

Marking: "POMONA HB-XX-*

RATINGS: (Entire Assembly)

Operating Temperature: +55°C (+131°F) Max

Voltage: Hand-held testing: 33VRMS/70VDC Max

Hands free testing in controlled voltage environments: 5000 WVDC Max

Current: 15 Amperes Cont.

Contact Res.: Less than .001 Ohms per Banana Plug

ORDERING INFORMATION: Model HB-XX-*

XX = Cable Lengths, Standard Lengths: 12" (305mm), 24" (610mm), 36" (914mm), 48" (1219mm)

Additional lengths can be quoted upon request.

* = Color, -0 Black, -2 Red.

Ordering Example: HB-48-2, Indicates 48" in length, color is Red

All dimensions are in inches. Tolerances (except noted): .xx = ± .02" (.51 mm), .xxx = ± .005" (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies.

Made in USA

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Pomona:

HB-48-6 HB-36-7