


REV. 0
DCO 143385

| | |
|-----------------|----------------------------|
| COIL: @ 25°C | |
| RESISTANCE | 200 OHMS ±10% |
| NOMINAL VOLTAGE | 6.0 VDC |
| MUST OPERATE | 3.4 VDC |
| MUST RELEASE | 2.0 VDC MAX, 0.28 VDC MIN. |

| | |
|--------------|--|
| ENVIRONMENT: | |
| VIBRATION | 10 Hz TO 3000 Hz @ 30 g's |
| SHOCK | 75 g's 6 MS. DURATION |
| TEMPERATURE | -65 °C TO +125 °C |
| NOTES: | OPERATE TIME 4.0 MS MAX. RELEASE TIME 7.5 MS MAX. CONTACT STABILIZATION TIME 2.0 MS MAX. |

CUSTOMER DATA SHEET



CONTACT RATING: LOW LEVEL TO 1A
28 VDC RESISTIVE 100,000 OPERATIONS

DR. B.D. 1/11/02 CK. *[Signature]* 1/11/02

CII Technologies
advanced control electronic solutions

CUST. OPL
CUST. NO. M39016/16-034P REV.

"JMSD" RELAY

JMSCD-6XP

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[JMSCD-6XP](#)