



Model #:	Ø Dimension "A"	Ø Dimension "B"	Accepts Wire AWG:
4933	.062" (1,57mm)	.160" (4,06mm)	18, 20, 22
4986	.120" (3,05mm)	.200" (5,08mm)	14, 16

FEATURES:

- Threaded two piece design allows wires to be soldered or crimped to the banana plug.
- Heavy-duty plastic body withstands cracking if accidentally dropped.
- Banana plug spring is nickel plated Beryllium Copper for long insertion life.
- Fits into Pomona Models 4921, 4934, and 4987 Sheathed Banana Jacks.

MATERIALS:

Banana Plug: Body – Brass, Nickel Plated

Spring – Beryllium Copper, Nickel Plated

Insulation: Nylon, Color per part number

Threaded Handle: Nylon, Color per part number, Marking: "POMONA ELECT. 4933 or 4986"

RATINGS:

Operating Voltage: 1200 Volts AC/DC

Current: 15 Amperes Max.

Operating Temperature: +80°C (+176°F)

ORDERING INFORMATION: Model 4933-* or 4986-*

* = Color, Standard Colors: -0 Black, -2 Red

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ± .005" (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies.

Made in USA

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Pomona:

[4933-0](#) [4986-2](#) [4986-0](#) [4933-2](#)