



Product: [8723](#)

Audio, Control & Instrument, #22-2pr, PO, Individ. Foil, PVC Jkt, CM

Product Description

Audio, Control & Instrument Cable, 22 AWG stranded (7x30) tinned copper conductors, polypropylene insulation, twisted pairs, individually Beldfoil® shielded (100% coverage), 24 AWG stranded tinned copper drain wire, PVC jacket.

Technical Specifications

Product Overview

Suitable Applications:	low voltage analog signals (4-20ma, 0-10v, ...); low voltage digital control (24v, ...); line level audio; computer communication; panel wiring
------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	No. of Pairs
22	7x30	TC - Tinned Copper	2

Conductor Count:	4
------------------	---

Insulation

Material	Nominal Wall Thickness
PP - Polypropylene	0.009 in

Color Chart

Number	Color
1	Red & Black
2	Green & White

Inner Shield Material

Type	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Tape	Alum / Poly	Beldfoil® (Z-Fold®-foil side out)	100 %	TC - Tinned Copper	24	7x32

Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.16 in	0.02 in

Electrical Characteristics

Conductor DCR

Individual Pair Nominal Shield DCR	Nominal Conductor DCR
15 Ohm/1000ft	14.7 Ohm/1000ft

Capacitance

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
33 pF/ft	62 pF/ft

Inductance

Nominal Inductance
0.17 µH/ft

Impedance

Nominal Characteristic Impedance

52 Ohm

High Frequency (Nominal/Typical)

Nom. Insertion Loss

10 dB/100m

Delay

Nominal Velocity of Propagation (VP) [%]

66 %

Current

Max. Recommended Current [A]

Per conductor @ 25°C (10C temperature rise): 2.3 A

Voltage

UL Voltage Rating

300 V RMS

Temperature Range

UL Temp Rating:	60°C
Operating Temp Range:	-20°C To +75°C

Mechanical Characteristics

Bulk Cable Weight:	17 lbs/1000ft
Max Recommended Pulling Tension:	42 lbs
Min Bend Radius/Minor Axis:	1.75 in

Standards

NEC Articles:	800
NEC/(UL) Specification:	CM
CEC/C(UL) Specification:	CM
CPR Euroclass:	Eca

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2004-01-01
MII Order #39 (China RoHS):	Yes

Suitability

Suitability - Indoor:	Yes
Suitability - Outdoor:	No

Flammability, LS0H, Toxicity Testing

UL Flammability:	UL1685 (UL Loading)
ISO/IEC Flammability:	IEC 60332-1-2
UL voltage rating:	300 V RMS

Plenum/Non-Plenum

Plenum (Y/N):	No
Plenum Number:	82723, 87723, 88723

Part Number

Variants

Item #	Color	Putup Type	Length	UPC/EAN
8723.0030	Chrome	Reel	30 m	8719605018571
8723.060100	Chrome	Reel	100 ft	612825214441
8723.00100	Chrome	Reel	100 m	8719605159229
8723.00U152	Chrome	UnReel	152 m	8719605018588
8723.01152	Chrome	Reel	152 m	8719605018601
8723.00U305	Chrome	UnReel	305 m	8719605018595
8723.01305	Chrome	Reel	305 m	8719605018632
8723.060500	Chrome	Reel	500 ft	612825214526
8723.060U500	Chrome	UnReel	500 ft	612825214434
8723.02500	Chrome	Reel	500 m	8719605018663
8723.01610	Chrome	Reel	610 m	8719605018656
8723.0601000	Chrome	Reel	1,000 ft	612825214458
8723.060U1000	Chrome	UnReel	1,000 ft	612825214410
8723.001000	Chrome	Reel	1,000 m	8719605018564
8723.011524	Chrome	Reel	1,524 m	8719605018618
8723.0601640	Chrome	Reel	1,640 ft	612825214496
8723.0602000	Chrome	Reel	2,000 ft	612825214502
8723.060U2000	Chrome	Reel	2,000 ft	612825214427
8723.013048	Chrome	Reel	3,048 m	8719605018625
8723.013050	Chrome	Reel	3,050 m	8719605018649
8723.0603280	Chrome	Reel	3,280 ft	612825214519
8723.0605000	Chrome	Reel	5,000 ft	612825214533
8723.06010000	Chrome	Reel	10,000 ft	612825214465
8723.06010001	Chrome	Reel	10,000 ft	612825214472
8723.0609999	Chrome	Reel	10,000 ft	612825214540
8723.06015000	Chrome	Reel	15,000 ft	612825214489

Footnote:	C - CRATE REEL PUT-UP.
-----------	------------------------

Footnote:	Y - FINAL PUT-UP LENGTH MAY VAR -10% TO +20% FROM LENGTH SHOWN. MAY CONTAIN 2 PIECES. MINIMUM LENGTH OF ANY ONE PIECE IS 1500'.
-----------	---------------------------------------------------------------------------------------------------------------------------------

History

Update and Revision:	Revision Number: 0.319 Revision Date: 04-28-2020
----------------------	--------------------------------------------------

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Belden Wire & Cable:

[8723 060U1000](#) [8723 060U2000](#) [8723 060U500](#) [8723 0601640](#) [8723 0603280](#)