


NOTES:

1. SHELL MATERIAL: BRASS ALLOY 360, 1/2 HARD.
2. SHELL FINISH: 200 μ" TIN/LEAD OVER 100 μ" NICKEL.
3. CONTACT MATERIAL: BERYLLIUM COPPER ALLOY 172, HEAT TREATED.
4. CONTACT FINISH: 30 μ" GOLD OVER 50 μ" NICKEL.
5. INSULATOR MATERIAL: GLASS FILLED POLYESTER, RATED UL 94 V-0.

	<p>MILL-MAX® MFG. CORP. P.O. BOX 300, 190 PINE HOLLOW RD, OYSTER BAY, N.Y. 11771-0300 TEL: (516) 922-6000, FAX (516) 922-9253, E-MAIL WWW.MILL-MAX.COM</p>
<p>ALL DIMENSIONS IN INCHES AND BEFORE PLATING</p>	<p>SCALE N/S</p>
<p>PIN TOLERANCES: LENGTHS ±.005 DIAMETERS ±.002 *ANGLES ±2°</p>	<p>DATE 01/08/02</p>
<p>INSULATOR TOLERANCES: LENGTHS ±.005 THICKNESS ±.003 HOLE TO HOLE ±.001 NOT ACCUMULATIVE</p>	<p>CHECKED DARREN</p>
<p>DIMENSIONS IN INCHES</p>	<p>ENG. APPROVAL DATE</p>
<p>TITLE</p>	<p>Steve Capitel</p>
<p>28 POSITION DIP CARRIER SOCK.</p>	<p>CUSTOMER APPROVAL</p>
<p>DATE</p>	<p>PROPOSAL NUMBER</p>
<p>PH-3727</p>	<p>REV -</p>

PLASTIC #P128-60-000-00-000000
 SUB-ASSY. #P600-00-628-00-000000
 ORDER AS: S682-93-628-30-270000

SECTION A-A

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Mill-Max:](#)

[682-93-628-30-270000](#)