


Printed-circuit board connector - PC 5/ 6-G-7,62 BK - 1763795

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

PCB headers, nominal current: 41 A, number of positions: 6, pitch: 7.62 mm, color: black, contact surface: Tin, mounting: Wave soldering



Key Commercial Data

Packing unit	50 pc
GTIN	 4 046356 411561
GTIN	4046356411561

Technical data

Dimensions

Pitch	7.62 mm
Dimension a	38.1 mm
Height	14.29 mm
Length of the solder pin	5 mm

General

Range of articles	PC 5/...-G
Rated voltage (III/3)	630 V
Connection in acc. with standard	EN-VDE
Nominal current I_N	41 A
Color	black
Number of positions	6

Standards and Regulations

Connection in acc. with standard	EN-VDE
	CUL

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Approvals

Approvals

Printed-circuit board connector - PC 5/ 6-G-7,62 BK - 1763795

Approvals

Approvals

EAC / cULus Recognized

Ex Approvals

Approval details

EAC		B.01742
-----	---	---------

cULus Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	E60425-19920722
	D	B	C
Nominal voltage UN	600 V	300 V	150 V
Nominal current IN	5 A	41 A	41 A

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Phoenix Contact:](#)

[1763795](#)