

ALUMINUM ELECTROLYTIC CAPACITORS

WD Chip Type, Low Impedance
High Temperature (260°C) Reflow
series



- Corresponding with 260°C peak reflow soldering
Recommended reflow condition : 260°C peak 5 sec. 230°C over 60 sec.
2 times ($\phi 10 \times 10 : 1$ time)
- Chip type, low impedance temperature range up to +105°C.
- Designed for surface mounting on high density PC board.
- Applicable to automatic mounting machine fed with carrier tape.
- Compliant to the RoHS directive (2011/65/EU).



Specifications

Item	Performance Characteristics							
Category Temperature Range	-55 to +105°C							
Rated Voltage Range	6.3 to 50V							
Rated Capacitance Range	1 to 1500 μ F							
Capacitance Tolerance	$\pm 20\%$ at 120Hz, 20°C							
Leakage Current	After 2 minutes' application of rated voltage, leakage current is not more than 0.01 CV or 3 (μ A), whichever is greater.							
Tangent of loss angle (tan δ)	Measurement frequency : 120Hz at 20°C							() is $\phi 8$ over
	Rated voltage (V)	6.3	10	16	25	35	50	
Stability at Low Temperature	Measurement frequency : 120Hz							
	Rated voltage (V)	6.3	10	16	25	35	50	
Endurance	The specifications listed at right shall be met when the capacitors are restored to 20°C after the rated voltage is applied for 5000 hours (2000 hours for $\phi D = 4, 5$ and 6.3) at 105°C.							
	Capacitance change	Within $\pm 30\%$ of the initial capacitance value						
Shelf Life	After storing the capacitors under no load at 105°C for 1000 hours and then performing voltage treatment based on JIS C 5101-4 clause 4.1 at 20°C, they shall meet the specified values for the endurance characteristics listed above.							
	Capacitance change	Within $\pm 10\%$ of the initial capacitance value						
Resistance to soldering heat	The capacitors are kept on a hot plate for 30 seconds, which is maintained at 250°C. The capacitors shall meet the characteristic requirements listed at right when they are removed from the plate and restored to 20°C.							
	tan δ	Less than or equal to the initial specified value						
Marking	Black print on the case top.							
	Leakage current	Less than or equal to the initial specified value						

Chip Type

($\phi 4$ to $\phi 6.3$)



($\phi 8$ to $\phi 10$)



Type numbering system (Example : 16V 22 μ F)



$\phi D \times L$	4 × 5.8	5 × 5.8	6.3 × 5.8	6.3 × 7.7	8 × 10	10 × 10
A	1.8	2.1	2.4	2.4	2.9	3.2
B	4.3	5.3	6.6	6.6	8.3	10.3
C	4.3	5.3	6.6	6.6	8.3	10.3
E	1.0	1.3	2.2	2.2	3.1	4.5
L	5.8	5.8	5.8	7.7	10	10
H	0.5 to 0.8	0.5 to 0.8	0.5 to 0.8	0.5 to 0.8	0.8 to 1.1	0.8 to 1.1

Voltage

V	6.3	10	16	25	35	50
Code	j	A	C	E	V	H

● Dimension table in next page.



■ Dimensions

Cap. (μ F)	V Code	6.3			10			16			25			35			50		
		0J			1A			1C			1E			1V			1H		
1	010																4 × 5.8	5.00	30
2.2	2R2																4 × 5.8	5.00	30
3.3	3R3																4 × 5.8	5.00	30
4.7	4R7													4 × 5.8	1.80	80	5 × 5.8	1.52	85
10	100										4 × 5.8	1.80	80	5 × 5.8	0.76	150	6.3 × 5.8	0.88	165
15	150							4 × 5.8	1.80	80	5 × 5.8	0.76	150	5 × 5.8	0.76	150	6.3 × 5.8	0.88	165
22	220				4 × 5.8	1.80	80	5 × 5.8	0.76	150	5 × 5.8	0.76	150	5 × 5.8	0.76	150	6.3 × 5.8	0.88	165
27	270	4 × 5.8	1.80	80	5 × 5.8	0.76	150	5 × 5.8	0.76	150	6.3 × 5.8	0.44	230	6.3 × 5.8	0.44	230	6.3 × 7.7	0.68	185
33	330	5 × 5.8	0.76	150	5 × 5.8	0.76	150	6.3 × 5.8	0.44	230	6.3 × 5.8	0.44	230	6.3 × 5.8	0.44	230	6.3 × 7.7	0.68	185
47	470	5 × 5.8	0.76	150	6.3 × 5.8	0.44	230	6.3 × 5.8	0.44	230	6.3 × 5.8	0.44	230	6.3 × 5.8	0.44	230	6.3 × 7.7	0.68	185
56	560	5 × 5.8	0.76	150	6.3 × 5.8	0.44	230	6.3 × 5.8	0.44	230	6.3 × 5.8	0.44	230	6.3 × 7.7	0.34	280	8 × 10	0.34	300
68	680	6.3 × 5.8	0.44	230	6.3 × 5.8	0.44	230	6.3 × 5.8	0.44	230	6.3 × 5.8	0.44	230	6.3 × 7.7	0.34	280	8 × 10	0.34	300
100	101	6.3 × 5.8	0.44	230	6.3 × 5.8	0.44	230	6.3 × 5.8	0.44	230	6.3 × 7.7	0.34	280	8 × 10	0.17	450	8 × 10	0.34	300
150	151	6.3 × 5.8	0.44	230	6.3 × 5.8	0.44	230	6.3 × 7.7	0.34	280	8 × 10	0.17	450	8 × 10	0.17	450	10 × 10	0.18	670
220	221	6.3 × 5.8	0.44	230	6.3 × 7.7	0.34	280	6.3 × 7.7	0.34	280	8 × 10	0.17	450	10 × 10	0.09	670	10 × 10	0.18	670
330	331	6.3 × 7.7	0.34	280	8 × 10	0.17	450	8 × 10	0.17	450	10 × 10	0.09	670	10 × 10	0.09	670			
470	471	8 × 10	0.17	450	8 × 10	0.17	450	8 × 10	0.17	450	10 × 10	0.09	670						
680	681	8 × 10	0.17	450	10 × 10	0.09	670	10 × 10	0.09	670									
1000	102	10 × 10	0.09	670	10 × 10	0.09	670												
1500	152	10 × 10	0.09	670															

Max. Impedance (Ω) at 20°C 100kHz,
Rated ripple current (mA_{rms}) at 105°C 100kHz

● Frequency coefficient of rated ripple current

Frequency	50 Hz	120 Hz	300 Hz	1 kHz	10 kHz or more
Coefficient	0.35	0.50	0.64	0.83	1.00

- Taping specifications are given in page 23.
- Recommended land size, soldering by reflow are given in page 18, 19.
- Please refer to page 3 for the minimum order quantity.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Nichicon:

[UWD0J101MCL1GS](#) [UWD0J102MCL1GS](#) [UWD0J151MCL1GS](#) [UWD0J152MCL1GS](#) [UWD0J221MCL1GS](#)
[UWD0J270MCL1GS](#) [UWD0J330MCL1GS](#) [UWD0J331MCL1GS](#) [UWD0J470MCL1GS](#) [UWD0J471MCL1GS](#)
[UWD0J560MCL1GS](#) [UWD0J680MCL1GS](#) [UWD0J681MCL1GS](#) [UWD1A101MCL1GS](#) [UWD1A102MCL1GS](#)
[UWD1A151MCL1GS](#) [UWD1A220MCL1GS](#) [UWD1A221MCL1GS](#) [UWD1A270MCL1GS](#) [UWD1A330MCL1GS](#)
[UWD1A331MCL1GS](#) [UWD1A470MCL1GS](#) [UWD1A471MCL1GS](#) [UWD1A560MCL1GS](#) [UWD1A680MCL1GS](#)
[UWD1A681MCL1GS](#) [UWD1C101MCL1GS](#) [UWD1C150MCL1GS](#) [UWD1C151MCL1GS](#) [UWD1C220MCL1GS](#)
[UWD1C221MCL1GS](#) [UWD1C270MCL1GS](#) [UWD1C330MCL1GS](#) [UWD1C331MCL1GS](#) [UWD1C470MCL1GS](#)
[UWD1C471MCL1GS](#) [UWD1C560MCL1GS](#) [UWD1C680MCL1GS](#) [UWD1C681MCL1GS](#) [UWD1E100MCL1GS](#)
[UWD1E101MCL1GS](#) [UWD1E150MCL1GS](#) [UWD1E151MCL1GS](#) [UWD1E220MCL1GS](#) [UWD1E221MCL1GS](#)
[UWD1E270MCL1GS](#) [UWD1E330MCL1GS](#) [UWD1E331MCL1GS](#) [UWD1E470MCL1GS](#) [UWD1E471MCL1GS](#)
[UWD1E560MCL1GS](#) [UWD1E680MCL1GS](#) [UWD1H010MCL1GS](#) [UWD1H100MCL1GS](#) [UWD1H101MCL1GS](#)
[UWD1H150MCL1GS](#) [UWD1H151MCL1GS](#) [UWD1H2R2MCL1GS](#) [UWD1H220MCL1GS](#) [UWD1H221MCL1GS](#)
[UWD1H270MCL1GS](#) [UWD1H3R3MCL1GS](#) [UWD1H330MCL1GS](#) [UWD1H4R7MCL1GS](#) [UWD1H470MCL1GS](#)
[UWD1H560MCL1GS](#) [UWD1H680MCL1GS](#) [UWD1V100MCL1GS](#) [UWD1V101MCL1GS](#) [UWD1V150MCL1GS](#)
[UWD1V151MCL1GS](#) [UWD1V220MCL1GS](#) [UWD1V221MCL1GS](#) [UWD1V270MCL1GS](#) [UWD1V330MCL1GS](#)
[UWD1V331MCL1GS](#) [UWD1V4R7MCL1GS](#) [UWD1V470MCL1GS](#) [UWD1V560MCL1GS](#) [UWD1V680MCL1GS](#)
[UUX2G4R7MNL1GS](#) [UWD1V221MCQ6GS](#) [UWD1H220MCQ1GS](#) [UWD1V101MCQ1GS](#) [UWD1H221MCQ1GS](#)
[UWD1V220MCQ1GS](#) [UWD1V221MCQ1GS](#)