

$\phi.030$
±.002
[0.76]


NOTES:

1. SUGGESTED MOUNTING HOLE = $\phi.130$



LEAD FINISH: GOLD PL.	
CASING FINISH: GOLD PL.	
CAPACITANCE	100pF MIN.
TEMP. RANGE	-55°C TO 125°C
CURRENT	10 AMP MAX.
WORKING VOLTAGE	125°C -- VAC MAX. 125°C 200 VDC MAX.
D.C. RESISTANCE	.01ohms MAX.
MIN. I.L. PER MIL-STD-220 AT 25°C NO LOAD	
FREQ. MHz	I.L. (db)
1	--
10	--
100	5
1 GHz	22
10 GHz	35

SCHEMATIC



MARKING:

PART: COLOR DOT: GREEN
BAG:

SCI-9980-101
DATE CODE
LOT NO.
QTY/BAG (200 MAX.)

00	REV. NO.	TOLERANCES UNLESS OTHERWISE SPECIFIED
CN 53065-ENG	CHANGE NOTICE	Fractions ± 1/64
		Dec. .xx±
		Dec. .xxx±.005
		Angles ±0° 30'
		CODE IDENT. NO. DLSP2

 SPECTRUM CONTROL INC.		FAIRVIEW PENNSYLVANIA
Dwn. KAUFFMAN	Description	
Date 2-22-10	FEEDTHRU FILTER	
Engr. B. DEVINE	SCI-9980-101	
Scale NONE		

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[API Technologies:](#)

[SCI-9980-101](#)